

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 32B TOBU 1M40G
Order No.	<u>1221070000</u>
Version	HDC enclosures, Size: 10, Protection degree: IP65, Plug housing, Cable entry from top, Side- locking clamp on lower side, Standard, Size of cable entries: M 40
GTIN (EAN)	4032248998180
Qty.	1 pc(s).
Qty.	1 pc(s).

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Dimensions and weights			
Width	98 mm	Width (inches)	3.858 inch
Height	79 mm	Height (inches)	3.11 inch
Depth	94 mm	Depth (inches)	3.701 inch
Net weight	394 g		
Temperatures			
Limit temperature	-40 °C 125 °C		
Environmental Product Co	mpliance		
REACH SVHC	Lead 7439-92-1		
Dimensions			
Cable entry	w threading	Height of housing P	79 mm
Cable entry Total length housing	w. threading 94 mm	Height of housing B Width housing C	82.5 mm
	54 1111	Width Housing C	02.3 mm
General data			
EMC housings	No	Housing main material	diecast aluminium
Material of locking element	Stainless steel, rust-proof	Protection degree	IP65
Surface finish	Powder coating	Tightening torque	2 Nm
Version			
Cable entry	w. threading	Clamp version	Side-locking clamp
Design	w. threading	Design of housing	Plug housing, Cable entry
Design	Standard	Design of notaling	from top
Design of locking system	Side-locking clamp on lower side	Internal thread	M 40
Number of cable entry on top	1	Number of cable entry sideways	0
Size	10	Size of cable entries	M 40
Suitable for ModuPlug [®]	Yes	Tightening torque	2 Nm
Top part/bottom part/lid	upper part	Туре	Plug
Classifications			
ETIM 6.0	EC000437	ETIM 7.0	EC000437
eClass 9.0	27-44-02-02	eClass 9.1	27-44-02-02
eClass 10.0	27-44-02-02	UNSPSC	30-21-18-01
Approvals			
Approvals	()		
ROHS	Conform		

Technical data

Downloads




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Brochure/Catalogue	FL FIELDWIRING EN
Engineering Data	EPLAN
Engineering Data	STEP
Technical Documentation	<u>1666870000_HDC_32B_TOBU_1PG29G_STP_Blatt1.pdf</u>

Creation date May 2, 2020 3:08:15 PM CEST

Drawings





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Bulkhead housing





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 32B ABU	Version
Order No.	<u>1217800000</u>	HDC enclosures, Size: 10, Protection degree: IP65, Open base, Side-
GTIN (EAN)	4008190148393	locking clamp on lower side, Standard
Qty.	1 pc(s).	

Coupling hood



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 32B KBU 1M40G	Version
Order No.	<u>1902730000</u>	HDC enclosures, Size: 10, Protection degree: IP65, Closed housing,
GTIN (EAN)	4032248585670	Side-locking clamp on lower side, Standard, Size of cable entries: M
Qty.	1 pc(s).	40
Туре	HDC 32B KBU 1PG36G	Version
Type Order No.	HDC 32B KBU 1PG36G <u>1902750000</u>	Version HDC enclosures, Size: 10, Protection degree: IP65, Closed housing,
··		

Creation date May 2, 2020 3:08:15 PM CEST

Accessories

Wei	dm	iill	or	╤

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Туре	HDC 32B KBU 1PG29G	Version
Order No.	<u>1902740000</u>	HDC enclosures, Size: 10, Protection degree: IP65, Closed housing,
GTIN (EAN)	4032248585687	Side-locking clamp on lower side, Standard, Size of cable entries: PG
Qty.	1 pc(s).	29

Bulkhead housing



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General	ordering	data
---------	----------	------

Contoral	or a or ing a a ta	
Туре	HDC 32B SBU 2PG36G	Version
Order No.	<u>1902640000</u>	HDC enclosures, Size: 10, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4032248585649	locking clamp on lower side, Standard, Size of cable entries: PG 36
Qty.	1 pc(s).	
Туре	HDC 32B SBU 2M32G	Version
Order No.	<u>1788460000</u>	HDC enclosures, Size: 10, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4032248205998	locking clamp on lower side, Standard, Size of cable entries: M 32
Qty.	1 pc(s).	
Туре	HDC 32B SBU 2PG29G	Version
Order No.	<u>1666920000</u>	HDC enclosures, Size: 10, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4008190424121	locking clamp on lower side, Standard, Size of cable entries: PG 29
Qty.	1 pc(s).	
Туре	HDC 32B SBU 1M32G	Version
Order No.	<u>1902600000</u>	HDC enclosures, Size: 10, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4032248585625	locking clamp on lower side, Standard, Size of cable entries: M 32
Qty.	1 pc(s).	
Туре	HDC 32B SBU 1PG36G	Version
Order No.	<u>1902610000</u>	HDC enclosures, Size: 10, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4032248585632	locking clamp on lower side, Standard, Size of cable entries: PG 36
Qty.	1 pc(s).	