

**SAI GHDE 30 S KU SI****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



There are three different enclosure sizes: 54mm width and 30mm width in both long and short versions. All the enclosures consist of the isolating plastic Pocan, which is very sturdy and resistant. The use of snap-in lugs allows easy disassembly so that quick troubleshooting is possible. Symbols, data, drawings or text can also be laser engraved on the enclosure surfaces as required.

**General ordering data**

Type	SAI GHDE 30 S KU SI
Order No.	<a href="#">1246820000</a>
GTIN (EAN)	4050118035100
Qty.	20 pc(s).

**SAI GHDE 30 S KU SI**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight	69.587 g
------------	----------

**Temperatures**

Operating temperature, max.	90 °C	Operating temperature, min.	-20 °C
-----------------------------	-------	-----------------------------	--------

**Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1, Potassium perfluorobutane sulfonate 29420-49-3
------------	--

**Technical specifications, empty housing**

Housing main material	PBT, PC	Protection degree	IP67, when fully mounted
Shielded	Yes		

**Classifications**

ETIM 6.0	EC001031	ETIM 7.0	EC001031
eClass 9.0	27-44-02-02	eClass 9.1	27-44-02-02
eClass 10.0	27-44-02-02		

**Approvals**

Approvals



ROHS	Conform
------	---------

**Downloads**

Brochure/Catalogue	<a href="#">CAT 8 SAI 15/16 EN</a> <a href="#">FL FIELDWIRING EN</a>
--------------------	---

**Data sheet**

**SAI GHDE 30 S KU SI**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

