

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com













Sensor/actuator cables are used for wiring sensors and actuators and for transmitting data or power in various applications. The moulded cable offers connected and tested connection of the plug-in connector to the cable ex-works. The cables may be exposed to a wide range of conditions, such as humidity, dust, heat, cold, shock or vibration.

Our developers have focused specifically on this issue and designed a host of different M8 and M12 sensor-actuator cables so you are bound to find the solution you need for your application.

Is there something you have not managed to find or you feel needs explanation? Talk to us!

General ordering data

Туре	SAIL-M12W-8-3.0U
Order No.	<u>1279420300</u>
Version	Sensor/actuator line, One end without connector, M12, Number of poles : 8, 3 m, pin, 90°, Shielded: No, LED: No, Sheath material: PUR, Halogen: No
GTIN (EAN)	4050118076455
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 147 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical specifications for cable

Number of poles	8
Outside diameter	$5.9 \text{ mm} \pm 0.2 \text{ mm}$
Shielded	No
Colour coding	blue, red, white, brown, green, yellow, grey, pink
Sheathing colour	black
Temperature range, moving	-2580 °C
Core in accordance with UL AWM style	
·	10493 (80 °C / 300 V)
Suitable for cable carriers	Yes
Bending radius, min., stationary	5 x cable diameter
Acceleration	5 m/s ²
Bending cycles	1 mill.
Configurable cable length	No

Core cross-section	0.25 mm ²
Cable length	3 m
Insulation	PP
Sheath material	
	PUR
Halogen	No
Temperature range, stationary	-4080 °C
Outer cladding in accordance with UL AWM style	20549 (80 °C / 300 V)
Torsion resistance	180 °/m
Bending radius, min., moving	10 x cable diameter
Speed	5 m/s
Resistant to welding beads	No

General technical data

AF size	12 mm
Connection thread	M12
Threaded ring material	Brass, nickel-plated
Protection degree	IP67, when screwed in
LED	No
Rated current	2 A
Temperature range of housing	-25+80 °C
Plugging cycles	≥ 100
jumpered	No

Version	pin, 90°
Housing main material	PUR
Coding	А
Contact surface	Gold-plated
Rated voltage	30 V
Insulation strength	10 ⁸ Ω
Tightening torque	M12: 0.8 - 1.2 Nm
Pollution severity	3

Standards

Connector standard	IFC 61076-2-101	Certificate no. (cUL us)	E307231

Classifications

ETIM 6.0	EC001855	ETIM 7.0	EC001855
eClass 9.0	27-06-03-11	eClass 9.1	27-06-03-11
eClass 10.0	27-06-03-11		

Approvals

Approvals



ROHS Conform



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Downloads

Brochure/Catalogue	<u>FL FIELDWIRING EN</u>	
Engineering Data	EPLAN, WSCAD	



Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26 D-32758 Detmold

Germany


Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Drawings


Dimensioned drawing



Pole scheme



Wiring diagram







Light, securely screwed-in round plug-in connectors. Screwty set DM / VPE: 1 / Order No.: 1920000000 Adapters: M12, M12 F, M8, M8 F



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Tool



Tools for stripping the sheathing from uncut power lines and outlet lines, plus screwdrivers for installing Pick-to-Light components.

General ordering data

Type SCREWTY-M12-DM
Order No. 1900001000
GTIN (EAN) 4032248436408

1 pc(s).

Version

Tools, Cable gland tool for moulded M12 lines

Tools

Qty.



- Stripping tools with automatic self-adjustment
- For flexible and solid conductors
- Ideally suitable for mechanical and plant engineering, railway and rail traffic, wind energy, robot technology, explosion protection as well as marine, offshore and ship building sectors
- Stripping length adjustable via end stop
- Automatic opening of clamping jaws after stripping
- No fanning-out of individual conductors
- · Adjustable to diverse insulation thicknesses
- Double-insulated cables in two process steps without special adjustment
- · No play in self-adjusting cutting unit
- Long service life
- · Optimised ergonomic design

General ordering data

Type STRIPPER 6-16 RED-LINE

9203110000 Stripp

GTIN (EAN) 4032248541423

Qty. 1 pc(s).

Order No.

Version

Stripping and cutting tool, 16mm²



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Cutting tools for outside diameters up to 22 mm



Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/IEC 60900.

General ordering data

Type KT 8
Order No. 9002650000
GTIN (EAN) 4008190020163
Oty. 1 pc(s).

Version

Cutting tools ,Cutting tool for one-hand operation

Blank



TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are five different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Preattachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the SMark laser printer, PrintJet ADVANCED, plotter, MC-Mobilo or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-lnk or STI pen in connection with CLI T sleeves

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type TM-I 18 MC NE GE
Order No. 1718431687
GTIN (EAN) 4008190349028
Qty. 320 pc(s).

Version

TM-I, Insert markers, 18 x 4 mm, yellow



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Type TM-I 18 MC NE WS
Order No. 1718431044
GTIN (EAN) 4008190349011
Oty. 320 pc(s).

Version

TM-I, Insert markers, 18 x 4 mm, white

Tools

Sheathing stripper for PVC cables



General ordering data

Type AM 12
Order No. 9030060000
GTIN (EAN) 4008190337827
Oty. 1 pc(s).

Version

Tools, Sheathing strippers, UTP and STP data cables

Screwty® cable gland tool with torque function



The ideal tool for any application

Screwty® is the ideal, all-purpose tool for tightening all common sensor and actuator cables. Even difficult-to-reach round plugs are accessible using the Screwty®. A simple turning movement tightens and loosens the connectors without the need for excessive force. The Screwty® is a unique and global solution since it fits with most cables and plugs from other vendors (over 90 %). The Screwty® consists of a handle with a conventional 1/4" adapter. Thus it can be used for all sizes: for M12 and M8 round plug-in connectors, and for M12F and M8F customisable plugs and sockets, as well as for all M23 plugs and sockets.

General ordering data

Туре SAI-SCREWTY BOX Order No. 1939180000 GTIN (EAN) 4032248615506 Qty. 1 pc(s). SCREWTY SW12 Туре 2598970000 Order No. 4050118781151 GTIN (EAN) Qty. 1 pc(s).

Version Tools, Bolting tool

Creation date May 2, 2020 10:21:10 PM CEST