

**SlimFix R
SFR 2/12 MC SDR**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



The Weidmüller range of conductor and cable marker products provides users with solutions for the most diverse applications. The range of applications extends from narrow conductors right up to cables with large outside diameters. Among the products in the range are combination systems with individual tags, transparent sleeves, shrink-fit sleeves and markers, which can be fixed with cable ties.

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| | |
|--------------------|--|
| Type | SFR 2/12 MC SDR |
| Order No. | 1318780000 |
| Version | SlimFix R, Conductor and cable markers, 2.2 - 2.9 mm, 12 x 5.8 mm, To customer specification |
| GTIN (EAN) | 4050118179583 |
| Qty. | 80 pc(s). |
| compatible printer | 1324380000 2438520000 2438510000 |

Data sheet

SlimFix R SFR 2/12 MC SDR

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Width | 5.8 mm | Width (inches) | 0.228 inch |
| Height | 12 mm | Height (inches) | 0.472 inch |
| Net weight | 0.173 g | | |

General data

| | | | |
|-----------------------------|--|---------------------------|---|
| Advice label | Colour based on customer requirements (Please send M-Print PRO file) | Colour | To customer specification |
| Halogen | No | Material | Polyamide 66 |
| Operating temperature range | -40...100 °C | Printed characters | Based on customer requirements (Please send M-Print PRO file) |
| Size of labelling field | 12 x 3.2 mm | UL 94 flammability rating | V-2 |
| Width | 5.8 mm | | |

Conductor and cable markers

| | | | |
|-------------------------------|----------------------|-------------------------------|---------------------|
| Conductor O.D. | 2.2 - 2.9 mm | Conductor O.D., max. | 2.9 mm |
| Conductor O.D., min. | 2.2 mm | Conductor cross-section, max. | 1.5 mm ² |
| Conductor cross-section, min. | 0.75 mm ² | Halogen | No |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| eClass 9.0 | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|------------------------------|
| Engineering Data | EPLAN, WSCAD |
|------------------|------------------------------|