

**PAC**  
**PAC-S1200-HE20-V0-0M5****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

The pre-assembled PAC cables establish an electrical and logical connection between the PLC and the PLC interfaces. These cables consist of the following components:

- Manufacturer's PLC connector.
- Multi-pole LIYY or LY YCY cable (shielded) with a cross-section of 0.14 mm<sup>2</sup> or 0.25 mm<sup>2</sup>.
- Flat cable connector, SUB-D or RSV, for connection to the interface.

The cables are tested automatically for their continuity and insulation to guarantee the functionality for which they have been designed.

**General ordering data**

Type	PAC-S1200-HE20-V0-0M5
Order No.	<a href="#">1329110005</a>
Version	Pre-assembled cable, PAC, Cable LiYY, 0.25 mm <sup>2</sup>
GTIN (EAN)	4032248331826
Qty.	1 pc(s).

## Data sheet

### PAC PAC-S1200-HE20-V0-0M5

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Net weight	99 g
------------	------

### General Data

Connector PLC side	2 x SIEMENS S7 1200 6ES7292-1AG30-0XA0 7P	Interface connector	HE10 20P
Number of poles, min.	20-pole	Outer diameter	10 ± 1 mm
Cable	Cable LiYY	Cable length	0.5 m
Material	PVC	Wire cross-section	0.25 mm <sup>2</sup>

### Classifications

ETIM 6.0	EC000237	ETIM 7.0	EC000237
eClass 9.0	27-24-22-20	eClass 9.1	27-24-22-20
eClass 10.0	27-24-22-20		

### Approvals

ROHS	Conform
------	---------