

Industrial Ethernet IE-MCT-1RS232/485-1SC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Product image



Serial/fibre-optic converter

Media converter for implementing serial, copper-based interfaces on fibre-optic cables and vice versa. Facilitates communication between terminal devices with type RS232/422/485 serial interface over a distance of up to 5 km.

- Ring and point-to-point transmission modes
- Extension of the RS232/422/485 transmission to up to 5 km
- Supports baud rates of 50 bps to 921.6 Kbps
- Expanded temperature range of -40 to 75°C
- Compact design

General ordering data

Type	IE-MCT-1RS232/485-1SC
Order No.	1344760000
Version	Serial/fibre-optic converter, 1 x terminal block for RS232/422/485, 1 x SC multimode, IP30, -40 °C...75 °C
GTIN (EAN)	4050118146837
Qty.	1 pc(s).

Creation date May 3, 2020 4:09:48 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

Industrial Ethernet IE-MCT-1RS232/485-1SC

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Width	90.2 mm	Width (inches)	3.551 inch
Height	100 mm	Height (inches)	3.937 inch
Depth	22 mm	Depth (inches)	0.866 inch
Net weight	130 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Serial interface

Baud rate	50 bit/s to 921.6 kbit/s	Connection type	1 removable 3-pole terminal block
Interface standards	RS-232/422/485	RS-485 data direction control	ADDC® (automatic data direction control)

fibre-optic interface

Receive sensitivity	-20 dBm	Transmission mode: "Point-to-point"	Half-duplex, Full-duplex
Transmission mode: "Ring"	Half-duplex	Transmit power	> - 5 dBm
Type of connection	SC connection, Multimode	Typical distances	5 km (50/125, 62.5/125, 100/140 µm multimode cable)
Wave length	850 nm		

EMC conformity and approvals

EMC standards	FCC Part 15 Class B, EN 61000-4-2 (ESD), Stage 3, EN 61000-4-3 (RS), Stage 2, EN 61000-4-4 (EFT), Stage 2, EN 61000-4-5 (Surge), Stage 3, EN 61000-4-6 (CS), EN 61000-4-8, Stage 1	Safety standard	UL 60950-1
---------------	--	-----------------	------------

Environmental conditions

Humidity	5 to 95 % (non-condensing)	Operating temperature, max.	75 °C
Operating temperature, min.	-40 °C	Storage temperature, max.	75 °C
Storage temperature, min.	-40 °C		

Guarantee

Time interval	5 years
---------------	---------

MTBF

MTBF	780,480 hrs	Database	Telcordia (Bellcore), GB
------	-------------	----------	--------------------------

Power supply

Connection type	1 removable 3-pole terminal block
Current consumption	140 mA @ 12 V DC
Overload current protection	1.1 A
Reverse polarity protection	Available

Creation date May 3, 2020 4:09:48 AM CEST

**Industrial Ethernet
IE-MCT-1RS232/485-1SC**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Supply line protection	2 KV Burst (EFT), EN6 1000-4-4, 2 KV Surge, EN6 1000-4-5		
Voltage supply	24 V DC		
Voltage supply range	Voltage type	DC	
	Voltage, min.	12 V	
	Voltage, max.	48 V	

Serial signals

RS-232	Tx, Rx, GND	RS-422	TxD+, TxD-, RxD+, RxD-, GND
RS-485 2-wire	Data+, Data-, GND	RS-485 4-wire	TxD+, TxD-, RxD+, RxD-, GND

Technical data

Housing main material	Aluminium	Protection degree	IP30
Type of mounting	Mounting plate, Wall mounting, when screwed in, TS 35, (with optional mounting kit IE-DINRAILMOUNT-KIT 1504430000)		

Classifications

ETIM 6.0	EC000310	ETIM 7.0	EC000310
eClass 9.0	19-17-01-14	eClass 9.1	19-17-01-14
eClass 10.0	19-17-04-11		

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Approval/Certificate/Document of Conformity	EU Declaration of Conformity
Brochure/Catalogue	CAT 9 IETH 18/19 EN
Engineering Data	STEP
User Documentation	Hardware Installation Guide

**Industrial Ethernet
IE-MCT-1RS232/485-1SC**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories**Mounting kit for DIN rail mounting**

Mounting kit for alternative fixing of Weidmüller serial/
fibre-optic cable converters (Article 1344760000 and
1362950000) to the DIN rail.

General ordering data

Type	IE-DINRAILMOUNT-KIT
Order No.	1504430000
GTIN (EAN)	4050118312263
Qty.	1 pc(s).