

**PAC
PAC-UNIV-HE20-HE20-2M5**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Similar to illustration

Cable preconfeccionado cable plano según IEC-603/
DIN41651.

- Cable plano - cable plano
- Cable plano - punteras

General ordering data

| | |
|------------|----------------------------|
| Type | PAC-UNIV-HE20-HE20-2M5 |
| Order No. | 1349670025 |
| Version | Pre-assembled cable, PAC |
| GTIN (EAN) | 4032248239429 |
| Qty. | 1 pc(s). |

Creation date May 3, 2020 4:36:52 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

Data sheet

PAC PAC-UNIV-HE20-HE20-2M5

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | |
|------------|-------|
| Net weight | 195 g |
|------------|-------|

Temperatures

| | | | |
|-----------------------------|-------------|-----------------------------|-------------|
| Operating temperature, max. | 50 °C | Operating temperature, min. | -10 °C |
| Storage temperature, max. | 60 °C | Storage temperature, min. | -10 °C |
| Operating temperature | -10...50 °C | Storage temperature | -10...60 °C |

Environmental Product Compliance

| | |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

General Data

| | | | |
|-----------------------|---------------------------------|---------------------|---------------------------------|
| Connector PLC side | FLAT CABLE CONECTOR HE10 20P | Interface connector | FLAT CABLE CONECTOR HE10 20P |
| Number of poles, min. | 20-pole | Outer diameter | 8.6 ± 1 mm |
| Cable | Cable LiYY | Cable length | 2.5 m |
| Material | PVC | Wire cross-section | 0.14 mm ² |

Electrical Data

| | | | |
|----------------------|---------------------|---|-----------|
| Rated voltage (text) | ≤ 60 V DC ≤ 25 V AC | Permissible current strength per path, max. | 1 A |
| Total current, max. | 3 A | Resistance | ≤ 150mΩ/m |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC000237 | ETIM 7.0 | EC000237 |
| eClass 9.0 | 27-24-22-20 | eClass 9.1 | 27-24-22-20 |
| eClass 10.0 | 27-24-22-20 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|