

**PAC  
PAC-UNIV-D9M-D9M-2M5**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Similar to illustration

Cable pre-confeccionado sub-d según IEC-807/  
DIN41652

- Sub-d a Sub-d
- Sub-d a punteras
- Cable apantallado

**General ordering data**

Type	PAC-UNIV-D9M-D9M-2M5
Order No.	<a href="#">1349750025</a>
Version	Pre-assembled cable, PAC, Cable LiYCY, 7,8 ± 1 mm
GTIN (EAN)	4032248306619
Qty.	1 pc(s).

Creation date May 3, 2020 4:51:10 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

# Data sheet

## PAC PAC-UNIV-D9M-D9M-2M5

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Net weight	358 g
------------	-------

### Temperatures

Operating temperature, max.	50 °C	Operating temperature, min.	-10 °C
Storage temperature, max.	60 °C	Storage temperature, min.	-10 °C
Operating temperature	-10...50 °C	Storage temperature	-10...60 °C

### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

### General Data

Connector PLC side	SUB-D MALE 9P	Interface connector	SUB-D MALE 9P
Number of poles, min.	9-pole	Outer diameter	7,8 ± 1 mm
Cable	Cable LiYCY	Cable length	2.5 m
Material	PVC	Wire cross-section	0.25 mm <sup>2</sup>

### Electrical Data

Rated voltage (text)	≤ 60 Vdc ≤ 25 Vac	Permissible current strength per path, max.	1 A
Total current, max.	3 A	Resistance	≤ 80 mΩ/m

### Classifications

ETIM 6.0	EC000237	ETIM 7.0	EC000237
eClass 9.0	27-24-22-20	eClass 9.1	27-24-22-20
eClass 10.0	27-24-22-20		

### Approvals

ROHS	Conform
------	---------