

**PAC  
PAC-UNIV-HE20-F-6M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Similar to illustration

Cable preconfeccionado cable plano según IEC-603/  
DIN41651.

- Cable plano - cable plano
- Cable plano - punteras

**General ordering data**

|            |                            |
|------------|----------------------------|
| Type       | PAC-UNIV-HE20-F-6M         |
| Order No.  | <a href="#">1349790060</a> |
| Version    | Pre-assembled cable, PAC   |
| GTIN (EAN) | 4032248189953              |
| Qty.       | 1 pc(s).                   |

Creation date May 3, 2020 4:55:17 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**PAC  
PAC-UNIV-HE20-F-6M**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

Net weight 409 g

**Temperatures**

|                             |             |                             |             |
|-----------------------------|-------------|-----------------------------|-------------|
| Operating temperature, max. | 50 °C       | Operating temperature, min. | -10 °C      |
| Storage temperature, max.   | 60 °C       | Storage temperature, min.   | -10 °C      |
| Operating temperature       | -10...50 °C | Storage temperature         | -10...60 °C |

**Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

**General Data**

|                       |   |                     |                                 |
|-----------------------|---|---------------------|---------------------------------|
| Connector PLC side    | H0.14/10 (FERRULES<br>0.14mm <sup>2</sup> ) | Interface connector | FLAT CABLE CONECTOR<br>HE10 20P |
| Number of poles, min. | 20-pole                                     | Outer diameter      | 8.6 ± 1 mm                      |
| Cable                 | Cable LiYY                                  | Cable length        | 6 m                             |
| Material              | PVC   | Wire cross-section  | 0.14 mm <sup>2</sup>            |

**Electrical Data**

|                      |                     |  |           |
|----------------------|---------------------|--|-----------|
| Rated voltage (text) | ≤ 60 V DC ≤ 25 V AC | Permissible current strength per path,<br>max. | 1 A       |
| Total current, max.  | 3 A                 | Resistance                                     | ≤ 150mΩ/m |

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000237    | ETIM 7.0   | EC000237    |
| eClass 9.0  | 27-24-22-20 | eClass 9.1 | 27-24-22-20 |
| eClass 10.0 | 27-24-22-20 |            |             |

**Approvals**

Approvals



ROHS Conform

**Downloads**

User Documentation [Colours chart](#)