

**PAC  
PAC-UNIV-HE34-F-10M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Similar to illustration

Cable preconfeccionado cable plano según IEC-603/  
DIN41651.

- Cable plano - cable plano
- Cable plano - punteras

**General ordering data**

Type	PAC-UNIV-HE34-F-10M
Order No.	<a href="#">1349840100</a>
Version	Pre-assembled cable, PAC
GTIN (EAN)	4032248267446
Qty.	1 pc(s).

Creation date May 3, 2020 5:01:19 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**PAC**  
**PAC-UNIV-HE34-F-10M**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight	1,364 g
------------	---------

**Temperatures**

Operating temperature, max.	50 °C	Operating temperature, min.	-10 °C
Storage temperature, max.	60 °C	Storage temperature, min.	-10 °C
Operating temperature	-10...50 °C	Storage temperature	-10...60 °C

**Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1
------------	----------------

**General Data**

Connector PLC side	H0.14/10 (FERRULES 0.14mm <sup>2</sup> )	Interface connector	FLAT CABLE CONECTOR HE10 34P
Number of poles, min.	34-pole	Outer diameter	11 ± 1 mm
Cable	Cable LiYY	Cable length	10 m
Material	PVC	Wire cross-section	0.14 mm <sup>2</sup>

**Electrical Data**

Rated voltage (text)	≤ 60 V DC ≤ 25 V AC	Permissible current strength per path, max.	1 A
Total current, max.	3 A	Resistance	≤ 150mΩ/m

**Classifications**

ETIM 6.0	EC000237	ETIM 7.0	EC000237
eClass 9.0	27-24-22-20	eClass 9.1	27-24-22-20
eClass 10.0	27-24-22-20		

**Approvals**

ROHS	Conform
------	---------

**Downloads**

User Documentation	<a href="#">Colours chart</a>
--------------------	-------------------------------