

**PAC
PAC-UNIV-D9F-D9F-1M5**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Similar to illustration

Cable pre-confeccionado sub-d según IEC-807/
DIN41652

- Sub-d a Sub-d
- Sub-d a punteras
- Cable apantallado

General ordering data

| | |
|------------|---|
| Type | PAC-UNIV-D9F-D9F-1M5 |
| Order No. | 1349870015 |
| Version | Pre-assembled cable, PAC, Cable LiYCY, 7,8 ± 1 mm |
| GTIN (EAN) | 4032248323579 |
| Qty. | 1 pc(s). |

Creation date May 3, 2020 5:02:39 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

Data sheet

PAC PAC-UNIV-D9F-D9F-1M5

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

| | |
|------------|---------|
| Net weight | 246.5 g |
|------------|---------|

Temperatures

| | | | |
|-----------------------------|-------------|-----------------------------|-------------|
| Operating temperature, max. | 50 °C | Operating temperature, min. | -10 °C |
| Storage temperature, max. | 60 °C | Storage temperature, min. | -10 °C |
| Operating temperature | -10...50 °C | Storage temperature | -10...60 °C |

Environmental Product Compliance

| | |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

General Data

| | | | |
|-----------------------|-----------------|---------------------|----------------------|
| Connector PLC side | SUB-D FEMALE 9P | Interface connector | SUB-D FEMALE 9P |
| Number of poles, min. | 9-pole | Outer diameter | 7,8 ± 1 mm |
| Cable | Cable LiYCY | Cable length | 1.5 m |
| Material | PVC | Wire cross-section | 0.25 mm ² |

Electrical Data

| | | | |
|----------------------|-------------------|---|-----------|
| Rated voltage (text) | ≤ 60 Vdc ≤ 25 Vac | Permissible current strength per path, max. | 1 A |
| Total current, max. | 3 A | Resistance | ≤ 80 mΩ/m |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC000237 | ETIM 7.0 | EC000237 |
| eClass 9.0 | 27-24-22-20 | eClass 9.1 | 27-24-22-20 |
| eClass 10.0 | 27-24-22-20 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|