

**PAC  
PAC-UNIV-D9M-D9F-3M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Similar to illustration

Cable pre-confeccionado sub-d según IEC-807/  
DIN41652

- Sub-d a Sub-d
- Sub-d a punteras
- Cable apantallado

**General ordering data**

|            |   |
|------------|---|
| Type       | PAC-UNIV-D9M-D9F-3M                               |
| Order No.  | <a href="#">1349950030</a>                        |
| Version    | Pre-assembled cable, PAC, Cable LiYCY, 7,8 ± 1 mm |
| GTIN (EAN) | 4032248193189                                     |
| Qty.       | 1 pc(s).  |

Creation date May 3, 2020 5:11:43 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

# Data sheet

## PAC PAC-UNIV-D9M-D9F-3M

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |       |
|------------|-------|
| Net weight | 413 g |
|------------|-------|

### Temperatures

|                             |             |                             |             |
|-----------------------------|-------------|-----------------------------|-------------|
| Operating temperature, max. | 50 °C       | Operating temperature, min. | -10 °C      |
| Storage temperature, max.   | 60 °C       | Storage temperature, min.   | -10 °C      |
| Operating temperature       | -10...50 °C | Storage temperature         | -10...60 °C |

### Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

### General Data

|                       |                 |                     |                      |
|-----------------------|-----------------|---------------------|----------------------|
| Connector PLC side    | SUB-D FEMALE 9P | Interface connector | SUB-D MALE 9P        |
| Number of poles, min. | 9-pole          | Outer diameter      | 7,8 ± 1 mm           |
| Cable                 | Cable LiYCY     | Cable length        | 3 m                  |
| Material              | PVC             | Wire cross-section  | 0.25 mm <sup>2</sup> |

### Electrical Data

|                      |                   |   |           |
|----------------------|-------------------|---|-----------|
| Rated voltage (text) | ≤ 60 Vdc ≤ 25 Vac | Permissible current strength per path, max. | 1 A       |
| Total current, max.  | 3 A               | Resistance                                  | ≤ 80 mΩ/m |

### Classifications

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000237    | ETIM 7.0   | EC000237    |
| eClass 9.0  | 27-24-22-20 | eClass 9.1 | 27-24-22-20 |
| eClass 10.0 | 27-24-22-20 |            |             |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|