

## VPU series

### VPU II 0 PV 1500V DC

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



#### Type II surge voltage arrester for use in photovoltaic applications

- Pluggable arrester
- Suitable for protecting DC systems
- High energy absorption with short response time
- Tested in accordance with EN 50539-11
- Suitable for use in accordance with IEC 60364-7-712 / EN 50539-12
- Coded voltage level
- Installation in distribution board
- Thermal protection function

#### General ordering data

Delivery status	<b>This article will no longer be available in the future.</b>
Available until	2022-12-31
Type	VPU II 0 PV 1500V DC
Order No.	<a href="#">1351480000</a>
Version	Surge voltage arrester, Low voltage, Accessories, 1500 V
GTIN (EAN)	4050118158632
Qty.	1 pc(s).
Alternative product	<a href="#">2530630000</a>

Creation date May 3, 2020 5:49:09 AM CEST

## Data sheet

### VPU series VPU II 0 PV 1500V DC

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Width	17.8 mm	Width (inches)	0.701 inch
Height	52 mm	Height (inches)	2.047 inch
Depth	64 mm	Depth (inches)	2.52 inch
Net weight	89.8 g		

### Temperatures

Operating temperature, min.	-40 °C	Storage temperature, max.	80 °C
Storage temperature, min.	-40 °C	Operating temperature	-40 °C...
Storage temperature	-40 °C...80 °C		

### General data

Colour	orange	Design	Installation housing; 1TE, Insta IP 20
Optical function display	green = OK; red = arrester is defective - replace	Protection degree	IP20
Rail	TS 35	UL 94 flammability rating	V-0

### Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	III
--------------------	---	------------------------	-----

### Photovoltaic technical data

Conditions and requirements	EN 50539-11	Maximum continuous operating voltage UCPV mode +/-, -/PE, +/PE	1,500 V DC
PV system voltage, max. $U_{cpv}$	1,500 V	Protection level $U_p$ at $I_n$ (per module)	≤ 5.2 kV
Protection level $U_p$ mode (+/-, -/PE, +/PE)	≤ 5.2 kV	Short-circuit current $I_{scpv}$	200 A
Standards	EN 50539-11		

### Connection data

Type of connection	pluggable
--------------------	-----------

### Classifications

ETIM 6.0	EC000941	ETIM 7.0	EC000941
eClass 9.0	27-13-08-05	eClass 9.1	27-13-08-05
eClass 10.0	27-13-08-05	UNSPSC	30-21-19-21

### Approvals

Approvals



ROHS Conform

**Data sheet****VPU series  
VPU II 0 PV 1500V DC**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data****Downloads**

---

Approval/Certificate/Document of Conformity	<a href="#">EAC VPU SERIES</a> <a href="#">CE PAPER</a> <a href="#">Declaration of Conformity</a> <a href="#">Declaration of Conformity</a>
Engineering Data	<a href="#">EPLAN_WSCAD</a>
User Documentation	<a href="#">Instruction sheet</a>

---

**Data sheet**

**VPU series**  
**VPU II 0 PV 1500V DC**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Drawings**

