

VPU series
VPU III R 24V/4KV AC/DC**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Similar to illustration

**Type III surge protection**

- Compact Type III arrester for AC/DC protection acc. to IEC 61643-11:2012
- Suitable for protecting terminals
- Installed in the vicinity of the equipment to be protected
- Can be used as single-port arrester when nominal current is greater than 16 A

General ordering data

Type	VPU III R 24V/4KV AC/DC
Order No.	1351580000
Version	Surge voltage arrester, Low voltage, with remote contact, Single-phase, $U_P(L/N-PE) \leq 220$ V
GTIN (EAN)	4050118158557
Qty.	1 pc(s).

Creation date May 3, 2020 5:50:06 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

VPU series

VPU III R 24V/4KV AC/DC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	18 mm	Width (inches)	0.709 inch
Height	102 mm	Height (inches)	4.016 inch
Depth	71.5 mm	Depth (inches)	2.815 inch
Net weight	84 g		

Temperatures

Humidity	5 - 95% rel. humidity	Operating temperature, max.	70 °C
Operating temperature, min.	-40 °C	Storage temperature, max.	70 °C
Storage temperature, min.	-40 °C	Operating temperature	-40 °C...70 °C
Storage temperature	-40 °C...70 °C		

Technical data, signal line

Rated current I_N	16 A
---------------------	------

Connection data, remote alert

Connection type	Screw connection	Max. torque	0.5 Nm
Stripping length	5 mm	Cross-section for connected wire, solid core, min.	0.2 mm ²
Cross-section for connected wire, solid core, max.	1.5 mm ²		

General data

Colour	orange	Design	Installation housing; 1TE, Insta IP 20
Optical function display	Green LED = OK, Red LED = arrester is defective, replace	Protection degree	IP20
Rail	TS 35	Segment	Power distribution
UL 94 flammability rating	V-0	Version	with remote contact

Insulation coordination acc. to EN 50178

Pollution severity	2	Surge voltage category	II
--------------------	---	------------------------	----

Rated data IEC / EN

Rated voltage (AC)	24 V	Rated voltage (DC)	32 V
Voltage type	AC/DC	Max. continuous voltage, U_c (AC)	32 V
Max. continuous voltage, U_c (DC)	42 V	Low voltage network	Single-phase
Discharge current, max. (8/20 μ s)	2 kA	Fuse	16 A
Short-circuit current rating I_{SCCR}	1.5 kA	Protection level U_p (typ.)	≤ 220 V
Protection level U_p at I_N (L/N-PE)	≤ 0.9 kV	Leakage current at U_n	30 μ A
Temporary surge voltage (over-voltage) - TOV	46 V	Combined pulse U_{OC}	4 kV
Mains frequency at 250 Vmax	50...60Hz	Number of poles	1
PE conductor current I_{PE}	30 μ A	Rated current I_N	16 A
Requirements category acc. to IEC 61643-11	Type III	Requirements class, acc. to EN 61643-11	T3
Response time	≤ 100 ns	Signalling contact	250 V 10 A 1 NC

VPU series

VPU III R 24V/4KV AC/DC

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Connection data

Type of connection	Screw connection	Stripping length, rated connection	7 mm
Tightening torque, min.	0.4 Nm	Tightening torque, max.	0.5 Nm
Clamping range, rated connection	2.5 mm ²	Clamping range, min.	0.5 mm ²
Clamping range, max.	2.5 mm ²	Wire cross-section, solid, min.	0.13 mm ²
Wire cross-section, solid, max.	2.5 mm ²	Wire connection cross-section, finely stranded, min.	0.5 mm ²
Wire connection cross section, finely stranded, max.	2.5 mm ²	Conductor cross-section, flexible, AEH (DIN 46228-1), min.	0.5 mm ²
Conductor cross-section, flexible, AEH (DIN 46228-1), max.	2.5 mm ²	Connection cross-section, stranded, min.	0.5 mm ²
Connection cross-section, stranded, max.	2.5 mm ²		

Classifications

ETIM 6.0	EC000941	ETIM 7.0	EC000941
eClass 9.0	27-13-08-05	eClass 9.1	27-13-08-05
eClass 10.0	27-13-08-05	UNSPSC	30-21-19-21

Approvals


Approvals



ROHS Conform

Downloads

Approval/Certificate/Document of Conformity	EAC VPU SERIES CE PAPER Declaration of Conformity
Brochure/Catalogue	CAT 4.4 ELECTR 16/17 EN
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP
User Documentation	Instruction sheet

Data sheet**VPU series**
VPU III R 24V/4KV AC/DC**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Drawings****Electric symbol**

Schematic circuit diagram

Data sheet**VPU series
VPU III R 24V/4KV AC/DC**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories**Crosshead screwdriver Phillips**

VDE insulated crosshead screwdriver, for Phillips screws, SDIK PH DIN 7438, ISO 8764/2-PH, output to ISO 8764-PH, SoftFinish grip

**General ordering data**

Type	SDIK PH0	Version
Order No.	9008560000	Screwdriver, Blade length: 60 mm
GTIN (EAN)	4032248056552	
Qty.	1 pc(s).	