

**Z-series  
ZQV 6/4 GE ZTL6**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Product image****Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

**General ordering data**

Type	ZQV 6/4 GE ZTL6
Order No.	<a href="#">1363030000</a>
Version	Z-series, Cross-connector, For the terminals, Number of poles: 4
GTIN (EAN)	4050118165449
Qty.	60 pc(s).

Creation date May 3, 2020 7:12:51 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

## Data sheet

### Z-series ZQV 6/4 GE ZTL6

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

Width	3.1 mm	Width (inches)	0.122 inch
Height	30.5 mm	Height (inches)	1.201 inch
Depth	33.96 mm	Depth (inches)	1.337 inch
Net weight	5.48 g		

### Temperatures

Storage temperature, max.	40 °C	Storage temperature, min.	10 °C
Storage temperature	10 °C...40 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	120 °C		

### Material data

Material	Wemid	Colour	yellow
UL 94 flammability rating	V-0		

### System specifications

Version	For the terminals
---------	-------------------

### Additional technical data

Explosion-tested version	No	Installation advice	Direct mounting
Type of fixing	Plugged		

### Dimensions

Pitch in mm (P)	8.1 mm
-----------------	--------

### Rating data

Rated current	41 A
---------------	------

### Classifications

ETIM 6.0	EC000489	ETIM 7.0	EC000489
eClass 9.0	27-14-11-40	eClass 9.1	27-14-11-40
eClass 10.0	27-14-11-40	UNSPSC	30-21-18-01

### Product information

Product information	Due to stability and temperature reasons It is only possible to break out 60% of contact elements The usage of cross connectors reduces the rated voltage to 400VThe voltage reduced to 25V if cut cross connection with blank cut edges are used
---------------------	---

### Approvals

ROHS	Conform
------	---------

### Downloads

Engineering Data	<a href="#">EPLAN</a>
Engineering Data	<a href="#">STEP</a>
User Documentation	<a href="#">StorageConditionsTerminalBlocks</a>

Creation date May 3, 2020 7:12:51 AM CEST