

**P-series  
TW PRV8 SDR**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Product image****DCS marshalling**

Our innovative PRV terminal blocks for DCS marshalling featuring a PUSH IN connection and our multifunctional DCS marshalling terminals featuring a screw connection (WMF) not only save space in the panel; they also guarantee more effective signal transmission in process control systems.

**General ordering data**

Type	TW PRV8 SDR
Order No.	<a href="#">1389230000</a>
Version	P-series, Separation plate, grey, 2 mm, Customer-specific printing
GTIN (EAN)	4050118189551
Qty.	10 pc(s).

Creation date May 3, 2020 8:45:20 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**P-series  
TW PRV8 SDR**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Width	2 mm	Width (inches)	0.079 inch
Height	120 mm	Height (inches)	4.724 inch
Depth	59.7 mm	Depth (inches)	2.35 inch
Net weight	9.5 g		

**Temperatures**

Storage temperature, max.	40 °C	Storage temperature, min.	10 °C
Storage temperature	10 °C...40 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	125 °C		

**Material data**

Material	Polycarbonate	Colour	grey
UL 94 flammability rating	V-0		

**System specifications**

Version	Customer-specific printing	Number of levels	8
---------	----------------------------	------------------	---

**Additional technical data**

Snap-on	Yes
---------	-----

**Classifications**

ETIM 6.0	EC000886	ETIM 7.0	EC000886
eClass 9.0	27-14-11-92	eClass 9.1	27-14-11-33
eClass 10.0	27-14-11-92		

**Approvals**

ROHS	Conform
------	---------

**Downloads**

Engineering Data	<a href="#">EPLAN, WSCAD, Zuken E3.S</a>
Engineering Data	<a href="#">STEP</a>
User Documentation	<a href="#">StorageConditionsTerminalBlocks</a>