

**SAIS-WDF-4-M20-T-COD****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Your peripheral devices should be supplied with greater power. With our new M12 plug-in connector, more than 250 V and 2 A is possible without problems. The compact S- and T-coded M12 plug-in connectors are designed for the transmission of up to 630 V AC or 60 V DC and 12 A.

**General ordering data**

Type	SAIS-WDF-4-M20-T-COD
Order No.	<a href="#">1392710000</a>
Version	Panel feed-through, Number of poles: 4, Coding: T, M12, 60 V
GTIN (EAN)	4050118193374
Qty.	1 pc(s).

Creation date May 3, 2020 8:53:52 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**SAIS-WDF-4-M20-T-COD****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight 28 g

**Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

**Standards**

Certificate No. (cURus) E307231

**General data**

Cable glands	M 20	Coding	T
Conductor O.D.	-	Conductor cross-section, max.	1.5 mm <sup>2</sup>
Conductor cross-section, min.	0.14 mm <sup>2</sup>	Connection thread	M12
Contact material	CuZn	Contact surface	Gold-plated
Housing main material	Zinc diecast	Insulation strength	10 <sup>8</sup> Ω
Number of poles	4	Plugging cycles	≥ 100
Pollution severity	3	Protection degree	IP67
Rated current	12 A	Rated current	12 A
Rated voltage	60 V	Rated voltage (text)	60 V
Shield connection	No	Temperature range of housing	-40 ... +85 °C
Type of connection	Screw connection		

**Classifications**

ETIM 6.0	EC002925	ETIM 7.0	EC002925
eClass 9.0	27-44-01-06	eClass 9.1	27-44-01-06
eClass 10.0	27-44-01-06		

**Approvals**

Approvals



ROHS Conform

**Downloads**
 Brochure/Catalogue [CAT 8 SAI 15/16 EN](#)  
[FL FIELDWIRING EN](#)

**SAIS-WDF-4-M20-T-COD**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Pole scheme**

