

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com







FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

Туре	IE-FC-SP-2ST/2D9
Order No.	<u>1450590000</u>
Version	FrontCom, Insert plate, shielded, 2x Data, 2x
	Signal
GTIN (EAN)	4050118255263
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Length	90.5 mm	Length (inches)	3.563 inch
Width	51.5 mm	Width (inches)	2.028 inch
Height	23 mm	Height (inches)	0.906 inch
Net weight	23.77 g		

Temperatures

Operating temperature, max.	70 °C	Operating temperature, min.	-40 °C	
Operating temperature	-40 °C70 °C			

Environmental Product Compliance

REACH SVHC	Potassium perfluorobutane
	sulfonate 29420-49-3

General data

Material	Polycarbonate PC	Product type	Insert plate, shielded
General standards			
Certificate No. (GERMLLOYD)	13866-15	Certificate No. (cURus)	E223801

Classifications

ETIM 6.0	EC000456	ETIM 7.0	EC000456
eClass 9.0	27-18-28-06	eClass 9.1	27-18-92-90
eClass 10.0	27-18-28-06	UNSPSC	31-16-23-03

Approvals

Approvals



ROHS		Confo
ROHS	(Conf

Downloads

Approval/Certificate/Document of Conformity	GL_FrontCom
Brochure/Catalogue	CAT 9 IETH 18/19 EN FL FIELDWIRING EN PI PROFINET CABLING EN
Engineering Data	<u>EPLAN</u>
Engineering Data	<u>STEP</u>
User Documentation	MAN IE GUIDE DE MAN IE GUIDE EN Designation key / Type key



Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Drawings

Dimensioned drawing







Industrial Ethernet

IE-FC-SP-2ST/2D9

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Accessories



Accessories

FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

General ordering data

Туре IE-FC-PWPC Order No. 1450820000 4050118255584 GTIN (EAN)

1 pc(s).

Version

FrontCom, Touch-safe protection

USB

Qty.



FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

Туре	IE-BI-USB-3.0-A	Version
Order No.	1487920000	USB insert, Flange insert, type A
GTIN (EAN)	4050118298208	
Qty.	10 pc(s).	
Туре	IE-BI-USB-AB	Version
Order No.	<u>1131380000</u>	USB insert, Flange insert, type AB
GTIN (EAN)	4032248911844	
Qty.	10 pc(s).	
Туре	IE-BI-USB-A	Version
Order No.	1019570000	USB insert, Flange insert, type A
GTIN (EAN)	4032248731602	
Qty.	10 pc(s).	



Industrial Ethernet

IE-FC-SP-2ST/2D9

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Blank



ESG is the tried-and-tested marker in MultiCard format for use on many well-known electrical devices. The result is high-quality device marking with a high-contrast appearance.

Various types are available for devices from the following manufacturers:

- Siemens
- Télémecanique
- ABB
- Beckhoff
- Lumberg
- · Tags for all-purpose usage; self-adhesive or clip-on tags, depending on the type

Advantages at a glance:

- Tags for universal usage, self-adhesive or clip-on tags, depending on type
- · For aligned equipment, e.g. circuit breakers, we supply ESG markers for clipping onto tag rails
- · Individual laser-quality printing according to specifications

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Please note that these markers are not intended for printing with the SpeedMarking laser.

General ordering data

ESG 7/20 SIRIUS MC NE WS Version

Order No. <u>1736181044</u> ESG, Device markers x 20 mm, PA 66, Colour: white, pluggable

GTIN (EAN) 4008190985950 200 pc(s). Qty.



Industrial Ethernet

IE-FC-SP-2ST/2D9

Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany Fon: +49 5231 14-0

Fax: +49 5231 14-292083 www.weidmueller.com

RJ45



FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

General ordering data

Туре	IE-BI-RJ45-FJ-B	Version
Order No.	<u>1963840000</u>	RJ45 insert socket, Connector for base, TIA-568B
GTIN (EAN)	4032248651894	
Qty.	10 pc(s).	
Туре	IE-BI-RJ45-FJ-P	Version
Order No.	<u>1963830000</u>	RJ45 insert socket, Connector for base, PROFINET
GTIN (EAN)	4032248646159	
Qty.	10 pc(s).	
Туре	IE-BI-RJ45-FJ-A	Version
Type Order No.	IE-BI-RJ45-FJ-A 1962850000	Version RJ45 insert socket, Connector for base, TIA-568A
Order No.	<u>1962850000</u>	
Order No. GTIN (EAN)	<u>1962850000</u> 4032248645053	
Order No. GTIN (EAN) Qty.	1962850000 4032248645053 10 pc(s).	RJ45 insert socket, Connector for base, TIA-568A
Order No. GTIN (EAN) Oty. Type	1962850000 4032248645053 10 pc(s). IE-BI-RJ45-C	RJ45 insert socket, Connector for base, TIA-568A Version

Signal - D-SUB



signal - D-SUB

FrontCom® Vario integrates multiple functions in only one single frame. The system is easy to install and you can select from a wide range of data, signal and power modules. In addition to being extremely compact, FrontCom® Vario offers a number of unique product features that will make your project planning and work activities secure, fast and future-proof. Furthermore, the FrontCom® Vario system has an attractive housing design that, by the way, offers highest impact-resistance and fully meets the requirements of IP 65 protection class.

Туре	IE-FCI-D9-FF	Version
Order No.	<u>1450840000</u>	FrontCom, Signal insert D-Sub, 9-pole, Socket / socket
GTIN (EAN)	4050118255737	
Qty.	1 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Туре	IE-FCI-D9-FM	Version
Order No.	<u>1450850000</u>	FrontCom, Signal insert D-Sub, 9-pole, Plug, Socket connector
GTIN (EAN)	4050118255713	
Qty.	1 pc(s).	
Туре	IE-FCI-D9-FS	Version
Order No.	<u>1450870000</u>	FrontCom, Signal insert D-Sub, 9-pole, Socket / solder connection
GTIN (EAN)	4050118255393	
Qty.	1 pc(s).	

Slotted screwdriver

Slotted screwdriver with rounded blade SD DIN 5265, ISO 2380/2, output to DIN 5264, ISO 2380/1. ChromTop tip, SoftFinish grip



Type S	SDS 0.4X2.5X75	Version
Order No. 9	0009030000	Screwdriver, Blade width (B): 2.5 mm, Blade length: 75 mm, Blade
GTIN (EAN) 4	1032248266944	thickness (A): 0.4 mm
Qty. 1	pc(s).	