

**VG Ex MS (Ex brass cable gland)  
VG M40 EXE MS**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Brass cable glands which are suitable for usage in explosion risk zone Ex e (Increased safety). They have been tested to the latest norms and standards EN 60079-0:2009, and also achieved the necessary ATEX certificate.

**General ordering data**

Type	VG M40 EXE MS
Order No.	<a href="#">1460090000</a>
Version	VG Ex MS (Ex brass cable gland), Cable glands, M 40, 18 mm, OD min. 22 - OD max. 32 mm, IP66, IP68, Brass, nickel-plated
GTIN (EAN)	4050118266207
Qty.	10 pc(s).

Creation date May 4, 2020 6:32:12 AM CEST

## Data sheet

### VG Ex MS (Ex brass cable gland) VG M40 EXE MS

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

## Technical data

### Dimensions and weights

Length	59 mm	Length (inches)	2.323 inch
Net weight	220 g		

### Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

### General information

Material	Brass, nickel-plated	External thread	M 40
Pitch of thread	1.5 mm	Length of thread	18 mm
AF size 1	45 mm	AF size 2	45 mm
Protection degree	IP66, IP68 - 6 bar (30 min.)	Protection degree with GWDR	IP66, IP68
Operating temperature range, min.	-40 °C	Operating temperature range, max.	100 °C
Outer cable diameter, min.	22 mm	Outer cable diameter, max.	32 mm
Clamp insert	Neoprene	O-Ring	NBR
Seal insert		Standards	EN 60079-0, EN 60079-1, EN 60079-7, EN 60079-11, EN 60079-31
Installation guidelines	CR See assembly instructions	Note: protection class	Please observe the information in the installation instructions.

### Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
eClass 9.0	27-14-44-32	eClass 9.1	27-14-44-34
eClass 10.0	27-14-44-32		

### Product information

Product information	In combination with Klippon STB enclosures an additional flat gasket must be used - GWDR NP.
---------------------	--

### Approvals

Approvals



Approvals	EAC; ATEX
ROHS	Conform

### Downloads

Brochure/Catalogue	<a href="#">CAT 5 ENCL 17/18 EN</a>
Engineering Data	<a href="#">EPLAN, WSCAD</a>
Engineering Data	<a href="#">STEP</a>

**VG Ex MS (Ex brass cable gland)  
VG M40 EXE MS**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Accessories**

**Brass nuts, standard, nickel-plated**



Weidmüller has a variety of different cable and wire entry systems in the Portfolio: with different designs of plastic, brass and stainless steel cable glands in the IP66, 67, 68 or IP69k protection classes. As a complete alternative to cable glands, pre-assembled cables with modular multi-wire or multi-cable entry systems can be simply and quickly inserted into electrical equipment. Last but not least, Weidmüller offers EX-certified cable glands and cable/wire entry systems.

- Cable glands made from plastic and brass
- EMC screwed joints
- for areas at risk of explosion
- VDE, CSA and UL approvals

**General ordering data**

Type	SKMU M40 MS	Version
Order No.	<a href="#">1737030000</a>	SKMU MS (brass locknut), Locknut, M 40, 4.5 mm, Brass, nickel-
GTIN (EAN)	4008190956509	plated
Qty.	50 pc(s).	