

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





Sensor/actuator cables are used for wiring sensors and actuators and for transmitting data or power in various applications. The moulded cable offers connected and tested connection of the plug-in connector to the cable ex-works. The cables may be exposed to a wide range of conditions, such as humidity, dust, heat, cold, shock or vibration.

Our developers have focused specifically on this issue and designed a host of different M8 and M12 sensor-actuator cables so you are bound to find the solution you need for your application.

Is there something you have not managed to find or you feel needs explanation? Talk to us!

General ordering data

Туре	SAIL-ZW-M12BW-3-5.0V
Order No.	<u>1466130500</u>
Version	Sensor/actuator line, Connecting line, M12 / M12, Number of poles : 3, 5 m, Twin cabling, Shielded: No, LED: No, Sheath material: PVC, Halogen: Yes
GTIN (EAN)	4050118275612
Qty.	1 pc(s).

Creation date May 4, 2020 6:05:50 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Dimensions and weights			
Net weight	385 g		
invironmental Product Comp	liance		
	L		
REACH SVHC	Lead 7439-92-1		
Fechnical specifications for c	able		
lumber of poles	3	Core cross-section	0.34 mm ²
Outside diameter	4.9 mm ± 0.2 mm	Cable length	5 m
Shielded	No	Insulation	PVC
Colour coding	brown, blue, black	Sheath material	PVC
Cheathing colour	black	Halogen	Yes
emperature range, moving	-580 °C	Temperature range, stationary	-3080 °C
Outer cladding in accordance with UL WM style	2464 (80 °C / 300 V)	Suitable for cable carriers	No
orsion resistance	0 °/m	Resistant to welding beads	No
Configurable cable length	No		
General technical data			
\F size	10	Versier	Turin cobling
	12 mm	Version	Twin cabling PUR
onnection thread	M12 / M12	Housing main material	
hreaded ring material	Diecast zinc	_ Coding	A
Protection degree	IP65, IP66, IP67, IP68, when screwed in	Contact surface	Gold-plated
ED	No	Rated voltage	250 V
lated current	4 A	Insulation strength	10 ⁸ Ω
emperature range of housing	-25+80 °C	Tightening torque	M12: 0.8 - 1.2 Nm
Plugging cycles	≥ 100	Pollution severity	3
umpered	No		
Standards			
Connector standard	IEC 61076-2-101	Certificate no. (cULus)	E307231
Classifications			
TIM 6.0	EC001855	ETIM 7.0	EC001855
Class 9.0	27-06-03-11	eClass 9.1	27-06-03-13
Class 10.0	27-06-03-11		
Approvals			
Approvals	~		
4-F	c(UL)us		
	LISTED		
ROHS	Conform		

Creation date May 4, 2020 6:05:50 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

Technical data

Downloads

Weidmüller 🕃	
--------------	--

Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Brochure/Catalogue	FL FIELDWIRING EN
Engineering Data	EPLAN, WSCAD
Product Change Notification	DE - Technische Änderung zu M12 Gewindering mit 6-Kant
	EN - Technical change to M12 nut with additional hexagonal mounting

Creation date May 4, 2020 6:05:50 AM CEST

Drawings

Dimensioned drawing






Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com


Dimensioned drawing



 Twin male connector, straight
 Angled socket

 Pole scheme
 Pole scheme

 3
 Image: Scheme in the schem





Light, securely screwed-in round plug-in connectors. Screwty set DM / VPE: 1 / Order No.: 1920000000 Adapters: M12, M12 F, M8, M8 F

Creation date May 4, 2020 6:05:50 AM CEST

Accessories

Tool



General ordering data

Туре	SCREWTY-M12-DM	Version
Order No.	<u>1900001000</u>	Tools, Cable gland tool for moulded M12 lines
GTIN (EAN)	4032248436408	
Qty.	1 pc(s).	

Tools



- · Stripping tools with automatic self-adjustment
- For flexible and solid conductors
- Ideally suitable for mechanical and plant engineering, railway and rail traffic, wind energy, robot technology, explosion protection as well as marine, offshore and ship building sectors
- Stripping length adjustable via end stop
- Automatic opening of clamping jaws after stripping
- No fanning-out of individual conductors
- Adjustable to diverse insulation thicknesses
- Double-insulated cables in two process steps without special adjustment
- No play in self-adjusting cutting unit
- Long service life

Light components.

Optimised ergonomic design

General ordering data

Туре	STRIPPER 6-16 RED-LINE	Version
Order No.	<u>9203110000</u>	Stripping and cutting tool, 16mm ²
GTIN (EAN)	4032248541423	
Qty.	1 pc(s).	

Weidmüller Interface GmbH & Co. KG

Weidmüller 🏵

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Tools for stripping the sheathing from uncut power lines and outlet lines, plus screwdrivers for installing Pick-to-

Creation date May 4, 2020 6:05:50 AM CEST



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Cutting tools for outside diameters up to 22 mm



Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/IEC 60900.

General ordering data

Туре	KT 8	Version
Order No.	9002650000	Cutting tools ,Cutting tool for one-hand operation
GTIN (EAN)	4008190020163	
Qty.	1 pc(s).	

Blank



TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are five different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Preattachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the SMark laser printer, PrintJet ADVANCED, plotter, MC-Mobilo or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-Ink or STI pen in connection with CLI T sleeves

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

 Type
 TM-I 18 MC NE GE

 Order No.
 1718431687

 GTIN (EAN)
 4008190349028

 Qty.
 320 pc(s).

TM-I, Insert markers, 18 x 4 mm, yellow

Creation date May 4, 2020 6:05:50 AM CEST

Version



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Туре	TM-I 18 MC NE WS	Version
Order No.	<u>1718431044</u>	TM-I, Insert markers, 18 x 4 mm, white
GTIN (EAN)	4008190349011	
Qty.	320 pc(s).	

Tools





General ordering data

Туре	AM 12	Version
Order No.	<u>9030060000</u>	Tools, Sheathing strippers, UTP and STP data cables
GTIN (EAN)	4008190337827	
Qty.	1 pc(s).	

Screwty® cable gland tool with torque function



The ideal tool for any application

Screwty® is the ideal, all-purpose tool for tightening all common sensor and actuator cables. Even difficult-to-reach round plugs are accessible using the Screwty®. A simple turning movement tightens and loosens the connectors without the need for excessive force. The Screwty® is a unique and global solution since it fits with most cables and plugs from other vendors (over 90 %). The Screwty® consists of a handle with a conventional 1/4" adapter. Thus it can be used for all sizes: for M12 and M8 round plug-in connectors, and for M12F and M8F customisable plugs and sockets, as well as for all M23 plugs and sockets.

General ordering data

Туре	SAI-SCREWTY BOX	Version
Order No.	<u>1939180000</u>	Tools, Bolting tool
GTIN (EAN)	4032248615506	
Qty.	1 pc(s).	
Туре	SCREWTY SW12	
Order No.	<u>2598970000</u>	
GTIN (EAN)	4050118781151	
Qty.	1 pc(s).	