

**KSPA (Klippon blanking plug, type A)  
KSPA M75 BNI**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



For sealing surplus threaded holes to maintain the IP class of protection

**General ordering data**

Available until	2014-05-20
Type	KSPA M75 BNI
Order No.	<a href="#">1477730000</a>
Version	KSPA (Klippon blanking plug, type A), Blanking plug, M 75, 17 mm, Brass, nickel-plated
GTIN (EAN)	4050118285680
Qty.	1 pc(s).

Creation date May 4, 2020 5:12:55 AM CEST

**KSPA (Klippon blanking plug, type A)  
KSPA M75 BNI**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data**
**Dimensions and weights**

Length	17 mm	Length (inches)	0.669 inch
Net weight	1,150 g		

**Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1
------------	----------------

**General information**

Material	Brass, nickel-plated	External thread	M 75
Pitch of thread	1.5 mm	Length of thread	17 mm
Coating	nickel-plated	Impact resistance	7 J ATEX version
Protection degree	IP54, IP66	Operating temperature range, min.	-100 °C
Operating temperature range, max.	400 °C	Standards	IEC 60079-0, IEC 60079-1, IEC 60079-7, IEC 60079-31, IEC 60529

Note: protection class

- All sealing plugs have a thread pitch of 1.5 mm.
- To obtain the specified IP rating, the through hole must comply with the regulations of EN 50262 Table 1 and it should be possible to secure the sealing plug in a suitable manner.
- On installation of the KSPA, the minimum number of engaged thread turns in line with the standard EN/IEC 60079-1, Section 5.3, must be observed.
- With NEC / CEC applications, it must be ensured that the "female" thread of the connection device into which the sealing plugs are screwed reveals at least 8 fully engaged thread turns.
- Operating instructions are enclosed with each sealing plug; these must be read prior to installation. The sealing plugs must be installed according to the specifications in the operating instructions.
- If KSPA sealing plugs are inserted into non-metallic Ex e connection devices, they must be connected to the system's earth circuit.

**Classifications**

ETIM 6.0	EC000451	ETIM 7.0	EC000451
eClass 9.0	27-14-44-25	eClass 9.1	27-14-44-35
eClass 10.0	27-14-44-25		

**Data sheet****KSPA (Klippon blanking plug, type A)  
KSPA M75 BNI**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data****Approvals**

Approvals



ROHS

Conform

**Downloads**

Brochure/Catalogue

[CAT 5 ENCL 17/18 EN](#)

Engineering Data

[EPLAN, WSCAD](#)

**KSPA (Klippon blanking plug, type A)  
KSPA M75 BNI**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Accessories**

**Brass nuts, standard, nickel-plated**



Weidmüller has a variety of different cable and wire entry systems in the Portfolio: with different designs of plastic, brass and stainless steel cable glands in the IP66, 67, 68 or IP69k protection classes. As a complete alternative to cable glands, pre-assembled cables with modular multi-wire or multi-cable entry systems can be simply and quickly inserted into electrical equipment. Last but not least, Weidmüller offers EX-certified cable glands and cable/wire entry systems.

- Cable glands made from plastic and brass
- EMC screwed joints
- for areas at risk of explosion
- VDE, CSA and UL approvals

**General ordering data**

Type	SKMU M75 MS	Version
Order No.	<a href="#">1737060000</a>	SKMU MS (brass locknut), Locknut, M 75, 8 mm, Brass, nickel-plated
GTIN (EAN)	4008190956530	
Qty.	5 pc(s).	

**Klippon® KSWN Nylon**



The KSWN is a flat seal made from nylon suitable for optional large-surface sealing of cable glands on enclosures or electrical cabinets.

**General ordering data**

Type	KSWN M75	Version
Order No.	<a href="#">1076670000</a>	KSWN (flat gasket - nylon), Sealing ring, M 75, Nylon 6
GTIN (EAN)	4032248838714	
Qty.	25 pc(s).	