

Industrial Ethernet IE-SR-2GT-LAN-FN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Product image



High performance industrial-security router

- Variations with 2 or 6 Gigabit ports
 - NAT masquerading, 1:1 network mapping and port forwarding
 - VPN function (u-link Remote Access Service, OpenVPN and IPsec)
 - Key switch function to control a WAN/VPN connection
-
- 6-port variations with expanded routing functionality
 - Variations with integrated 4G/LTE modem for high-speed, internet-based mobile communications access
 - Cost-efficient variation without VPN functionality for NAT and security applications (1489940000, IE-SR-2GT-LAN-FN)
 - Variations with DNV-GL approval for use in a maritime environment

General ordering data

Type	IE-SR-2GT-LAN-FN
Order No.	1489940000
Version	Security/NAT Router, Gigabit Ethernet, 2x RJ45 10/100/1000BaseT(X), IP20, -20 °C...70 °C
GTIN (EAN)	4050118299533
Qty.	1 pc(s).

Industrial Ethernet IE-SR-2GT-LAN-FN

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Width	35 mm	Width (inches)	1.378 inch
Height	170 mm	Height (inches)	6.693 inch
Depth	140 mm	Depth (inches)	5.512 inch
Net weight	700 g		

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Network Services/Firewall/Management

Firewall	IPv4 Stateful Packet Inspection Firewall (incoming/outgoing), NAT masquerading, 1:1 NAT, Port forwarding, layer 2/3 filter (VLAN ID, VLAN QoS Tag, MAC address, EtherType frame), Auto-learning function to create packet filter rules (analysis of network traffic), Layer 2/3-based packet prioritisation (Ethernet Frame, IP Header, VLAN Tag)	Management	Configuration via WEB interface (HHTTP/HTTPS), Language interface can be switched to German or English, Configuration support through detailed help information (tool tip), Configurable multi-user access with freely definable rights, Support for SNMP v1/v2/v3, event log/syslog
Network services	DHCP Server / DHCP Relay, DNS relay, NTP client, DynDNS (DHCP client acc. to RFC 2136)		

DSL and UMTS/HSPA

DSL	Connection of DSL modem via LAN or WAN port, Free configuration of PPPoE access data	DynDNS	Support for automatic registration
-----	--	--------	------------------------------------

Miscellaneous

Diagnostics	Remote capture function for network diagnostics via a connected PC (Wireshark)	Modbus/TCP	Integral modbus TCP server for status queries
Monitoring	Client monitoring (per ICMP) with alarm function in the event of a fault		

Modes of operation

IP router	IP routing (IPv4, Layer-3) with SPI firewall (Stateful Packet Inspection)	Transparent bridge	2-port switch with additional layer-2 filter
-----------	---	--------------------	--

**Industrial Ethernet
IE-SR-2GT-LAN-FN**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
EMC conformity and approvals

EMC standards	FCC Part 15, Class A, EN 61000-6-4, EN 61000-6-2	Safety standard	UL508
Shock	according to IEC 60068-2-27	Vibration	according to IEC 60068-2-6

Environmental conditions

Humidity	5 - 90 %, no condensation	Operating temperature, max.	70 °C
Operating temperature, min.	-20 °C	Storage temperature, max.	85 °C
Storage temperature, min.	-20 °C		

Guarantee

Time interval	3 years
---------------	---------

Interfaces

Digital inputs	Cut: physically disconnects (Link Down) the WAN port (24 V in)	Digital outputs	Alarm: indicates a configurable network state or fault (24 V out)
LED indicator	Indication of voltage status, Status, Section, Alarm	Number of ports	2x RJ45 10/100/1000BaseT(X)
RJ45 ports	10/100/1000BaseT(X), auto negotiation, Full-/half-duplex mode	Reset button	Restoration of factory settings
SCM card reader	Save and restore the configuration using smart card (memory chip)	USB port	USB 2.0 interface for firmware update or restoration of the device configuration via USB flash drive

MTBF

MTBF	135,270 hrs
------	-------------

Power supply

Current consumption	max. 0.6 A at 24 V DC	Voltage supply	1x 24 V DC (7 to 36 V DC), NEC class 2, (for use in conformity with UL specifications: 7 - 30 V DC)
---------------------	-----------------------	----------------	---

Technical data

Housing main material	diecast aluminium	Protection degree	IP20
Type of mounting	DIN rail, VESA 75		

Classifications

ETIM 6.0	EC001478	ETIM 7.0	EC001478
eClass 9.0	19-17-01-03	eClass 9.1	19-17-01-03
eClass 10.0	19-17-04-05		

Data sheet**Industrial Ethernet
IE-SR-2GT-LAN-FN**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data**Approvals**

Approvals



ROHS

Conform

Downloads

Approval/Certificate/Document of Conformity	EU Declaration of Conformity
Brochure/Catalogue	CAT 9 IETH 18/19 EN
Engineering Data	STEP
Product Change Notification	Firmware Release Notes
Software	SNMP MIB file Firmware - Version 3.5.0
User Documentation	Hardware Installation Guide Manual User Note - Secure Router Configuration

Industrial Ethernet IE-SR-2GT-LAN-FN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

Mounting kit for 19" rack assembly

- For assembling DIN rail-based devices on 19" racks



General ordering data

Type	RM-KIT	Version
Order No.	1241440000	Kit for 19"-rack mounting
GTIN (EAN)	4050118029154	
Qty.	1 pc(s).	

Ethernet (Cat.6)



- Suitable for Cat. 5 (up to 100 MHz) and Cat. 6 (up to 250 MHz Class E)
- Suitable for PoE+ (according to IEEE 802.3at, IEEE 802.3bt Type 3 and 4)
- Protection of all wire pairs
- Connection via RJ45 sockets
- Metal housing

General ordering data

Type	VDATA CAT6	Version
Order No.	1348590000	Terminal rail fixing, Surge protection, 1 A, According to IEC61643-21
GTIN (EAN)	4050118153002	
Qty.	1 pc(s).	