Automation Products - u-remote IP20 UR20-EM-1315180000-SP



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Similar to illustration



More performance. Simplified. u-remote.

Weidmüller u-remote – our innovative remote I/O concept with IP 20 which focuses purely on user benefits: tailored planning, faster installation, safer start-up, no more downtime. For considerably improved performance and greater productivity.

Reduce the size of your cabinets with u-remote, thanks to the narrowest modular design on the market and the need for fewer power-feed modules. Our u-remote technology also offers tool-free assembly, while the modular "sandwich" design and integrated web server speed up installation, both in the cabinet and machine. Status LEDs on the channel and each u-remote module enable reliable diagnosis and rapid service.

This and many other amazing ideas boost the availability of your machines and systems. And ensure smooth processes too. From planning to operation.

u-remote stands for "More Performance". Simplified

General ordering data

Type UR20-EM-1315180000-SP Order No. 1490220000 Version Replacement part GTIN (EAN) 4050118299588 Qty. 1 pc(s).				
Version Replacement part GTIN (EAN) 4050118299588	Туре	UR20-EM-1315180000-SP		
GTIN (EAN) 4050118299588	Order No.	<u>1490220000</u>		
	Version	Replacement part		
Qty. 1 pc(s).	GTIN (EAN)	4050118299588		
· · · · · · · · · · · · · · · · · · ·	Qty.	1 pc(s).		

Creation date May 4, 2020 4:35:21 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

Automation Products - u-remote IP20 UR20-EM-1315180000-SP

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Dimensions and weights					
Net weight	28 g				
Environmental Prod	uct Compliance				
REACH SVHC	Lead 7439-92-1				
Classifications					
ETIM 6.0	EC002584	ETIM 7.0	EC002584		
eClass 9.0	27-33-02-92	eClass 9.1	27-24-26-90		
eClass 10.0	27-33-02-92				