

MetalliCard SFX-M 17/60-5 ST SDR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





MetalliCards are available in aluminium or stainless steel to meet a wide range of labelling requirements. The chrome-coated aluminium tags are the inexpensive alternative for a variety of applications, and in particular, they prove themselves through the deep contrasts of their multi-colour print.

In the technologically demanding chemical and process industries, you are on the safe side when using the stainless steel MetalliCard with its outstanding resistance characteristics. Its formats cover the needs of the entire system-identification spectrum. Whether small equipment or type plates, they ensure high-quality marking processes. The MetalliCard also offers optimum installation characteristics. MetalliCards can be used universally thanks to various fixation options: bonding, riveting, with tag holders or rails, or in combination with stainless steel cable ties.

A special punching in the SFX-M allows the use of steel cable ties.

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| Туре | SFX-M 17/60-5 ST SDR | | |
|--------------------|---|--|--|
| Order No. | <u>1505240000</u> | | |
| Version | MetalliCard, Conductor and cable markers, 7 - 40 mm, 60 x 17 mm | | |
| GTIN (EAN) | 4050118313697 | | |
| Qty. | 1 pc(s). | | |
| compatible printer | <u>1324380000</u> | | |



MetalliCard SFX-M 17/60-5 ST SDR

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Downloads

Engineering Data

| Zimononono ana tronginto | | | |
|-------------------------------|---|-------------------------------|---------------------|
| | | | |
| Width | 17 mm | Width (inches) | 0.669 inch |
| Height | 60 mm | Height (inches) | 2.362 inch |
| Depth | 0.8 mm | Depth (inches) | 0.031 inch |
| Net weight | 1.95 g | | |
| General data | | | |
| | | | |
| Material | Micro-etched stainless steel 1.4301 (ST) | Operating temperature range | -55130 °C |
| Printed characters | Based on customer requirements (Please send M-Print PRO file) | Recommended industries | Process, Energy |
| Width | 17 mm | - | Flocess, Ellergy |
| vidui | 17 111111 | | |
| Conductor and cable mark | ers | | |
| | | | |
| Conductor O.D. | 7 - 40 mm | Conductor O.D., max. | 40 mm |
| Conductor O.D., min. | 7 mm | Conductor cross-section, max. | 500 mm ² |
| Conductor cross-section, min. | 16 mm ² | | |
| Classifications | | | |
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| eClass 9.0 | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 | | |
| Approvals | | | |
| ROHS | Conform | | |
| nurio | Comorm | | |

EPLAN, WSCAD



MetalliCard SFX-M 17/60-5 ST SDR

Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

MetalliCard



Flexible printing on plastic and metal markers

The PrintJet ADVANCED is an inkjet printer which prints on plastic markers in MultiCard format and metal markers of the MetalliCard family. Thanks to its high loader capacity, it is ideal for printing large volumes in continuous operation. The precise colour printing and thermal fixing guarantee optimum print results for the durable identification of equipment. With these properties, the PrintJet ADVANCED brings efficiency to the operating process – whether operated with the M-Print® PRO software or as a stand-alone solution with preconfigured print templates.

Your benefits at a glance:

- Precise colour printing
- Serial printing of metal markers
- High level of automation thanks to loader capacity of 30 MultiCards
- · Durable and robust markers thanks to thermal fixing
- User-friendly operation thanks to intuitive touch display
- · Can be used as stand-alone solution

General ordering data

Type PRIMER CC-M
Order No. 2068020000
GTIN (EAN) 4050118416534
Oty. 100 pc(s).