

**FAD
FAD BLK1 SL24**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Similar to illustration

The front adapters for migration are connected to the old PLC and, by means of a new pre-assembled cable, to the new one. Some adapters have 2 connectors for redundancy.

General ordering data

Type	FAD BLK1 SL24
Order No.	1505520000
GTIN (EAN)	4050118319538
Qty.	1 pc(s).

FAD
FAD BLK1 SL24

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Length	209.2 mm	Length (inches)	8.236 inch
Width	37 mm	Width (inches)	1.457 inch
Height	24 mm	Height (inches)	0.945 inch
Net weight	404.33 g		

Temperatures

Operating temperature, max.	50 °C	Operating temperature, min.	-25 °C
Storage temperature, max.	60 °C	Storage temperature, min.	-40 °C
Operating temperature	-25...50 °C	Storage temperature	-40...60 °C

Connection data

Connection (field side)	SL 5.08 mm	Connection to PLC	TSX-BLK1
-------------------------	------------	-------------------	----------

Ratings data

Operating voltage	230 V AC / 320 V DC
-------------------	---------------------

Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	230 V AC
Surge voltage category	II	Pollution severity level	2
Pulse voltage test (1,2/50µs)	2.1 kV	Insulation test voltage	1.2 kVAC

Classifications

ETIM 6.0	EC002584	ETIM 7.0	EC002584
eClass 9.0	27-33-02-92	eClass 9.1	27-24-22-92
eClass 10.0	27-33-02-92		

Approvals

Approvals



ROHS Conform

DownloadsEngineering Data [EPLAN](#)

Data sheet

**FAD
FAD BLK1 SL24**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

