

FP MONO LED K DC SA**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Energy-efficient basic lighting with a long service life**

- LED lamp for harsh environmental conditions (shocks and vibration, temperature range)
- higher energy efficiency and service life than fluorescent lamps
- Can be used worldwide thanks to the multi-voltage input (24 V... 120 VDC)
- high fire protection classification V0
- Beam direction to one side

Versions

- Pluggable from 0.5 mm² to 2.5 mm²
- Pre-assembled 2.5 mm²

General ordering data

Type	FP MONO LED K DC SA
Order No.	1507040000
GTIN (EAN)	4050118315547
Qty.	1 pc(s).

FP MONO LED K DC SA

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Length	208 mm	Length (inches)	8.189 inch
Width	104 mm	Width (inches)	4.094 inch
Height	55 mm	Height (inches)	2.165 inch
Net weight	602 g		

Temperatures

Humidity	92 % @ 25 °C	Operating temperature, max.	70 °C
Operating temperature, min.	-40 °C	Storage temperature, max.	85 °C
Storage temperature, min.	-40 °C	Operating temperature	-40 °C...70 °C
Storage temperature	-40 °C...85 °C		

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

General data

Amplitude of acceleration	5 m/s ² (@ 9-200 Hz)	Amplitude of deflection	1.5 mm (2-9 Hz)
Efficiency class (according to EU Directive No. 874/2012)	A	Halogen	yes (PVC cable)
Height	≤ 3000 m	Insulation voltage	< 500 V (housing/PE)
LED operating life	> 50.000 h	Light colour (CCT)	Cool White, 6000K
Light current	454 lm	Line type	Heluwind WK 103w-Torsion 2x2.5 mm ²
Mounting position, installation notice	Arbitrary	Peak acceleration, type L	70 m/s ²
Pollution severity	2	Pre-assembled connector cross-section	2.5 mm ²
Protection class	II	Protection degree	IP54
Shock resistance EN 60721-3-3	Class 3M3 portable	Short-circuit protection	Yes, internal
Silicone	No	Surge voltage category	II
Type of connection	Open cable end/length 2 m	UL 94 flammability rating	V-0
Vibration resistance EN 60721-3-3	Class 3M3 sinusoidal, stationary		

EMC

Interference immunity test acc. to Acc. to EN 61547 Interference radiation acc. to EN 55015

Rated data acc. to IEC 60598-1

DC input voltage range	24...120 V DC	Input voltage	21.6 V ... 144 V DC / protected against reverse polarity
Power rating	5 W	Rated current DC	0.2 A @ 24 V DC

Classifications

ETIM 6.0	EC001959	ETIM 7.0	EC001959
eClass 9.0	27-11-06-40	eClass 9.1	27-11-06-40
eClass 10.0	27-11-06-40		

Data sheet

FP MONO LED K DC SA

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Approvals

Approvals



ROHS

Conform