

**TM**  
**TM 203/23 V0****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

Our extensive range of TM sleeves is suitable for all-purpose use. They cover a wide range of applications: from thin conductors to cables with large external diameters. This range offers printed inlay tags with maximum protection against outside influences. TM sleeves permit flexible installation. There are five different lengths (12, 15, 18, 20 and 30 mm) and eleven sizes - a marker type for all sleeves.

- Optimum protection for printed inlay tags
- Wide range of applications for conductors and cables
- One tag type for all cross-sections
- TMX 30 for mounting with cable ties (width 4.6 mm)

**General ordering data**

|            |  |
|------------|--|
| Type       | TM 203/23 V0   |
| Order No.  | <a href="#">1507080000</a>   |
| Version    | TM, Socket x 6 mm, PVC, Colour: Transparent,<br>Conductor O.D.: 4 - 6 mm |
| GTIN (EAN) | 4050118315554  |
| Qty.       | 500 pc(s).   |

Creation date May 4, 2020 2:32:33 AM CEST

**TM**  
**TM 203/23 V0**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |         |                 |            |
|------------|---------|-----------------|------------|
| Width      | 6 mm    | Width (inches)  | 0.236 inch |
| Height     | 23 mm   | Height (inches) | 0.906 inch |
| Net weight | 0.768 g |                 |            |

**General data**

|                             |             |                           |                           |
|-----------------------------|-------------|---------------------------|---------------------------|
| Colour                      | Transparent | Material                  | PVC                       |
| Operating temperature range | -40...80 °C | Recommended industries    | Transportation, Machinery |
| Type of printing            | neutral     | UL 94 flammability rating | V-0                       |
| Width                       | 6 mm        |                           |                           |

**Conductor and cable markers**

|                               |                     |                               |                    |
|-------------------------------|---------------------|-------------------------------|--------------------|
| Conductor O.D.                | 4 - 6 mm            | Conductor O.D., max.          | 6 mm               |
| Conductor O.D., min.          | 4 mm                | Conductor cross-section, max. | 10 mm <sup>2</sup> |
| Conductor cross-section, min. | 2.5 mm <sup>2</sup> |                               |                    |

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0   | EC001530    |
| eClass 9.0  | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 |            |             |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                             |  |
|-----------------------------|--|
| Engineering Data            | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>   |
| Engineering Data            | <a href="#">STEP</a>   |
| Product Change Notification | <a href="#">PCN Transparent Sleeves_DE</a><br><a href="#">PCN Transparent Sleeves_EN</a> |

**TM**  
**TM 203/23 V0**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Accessories**
**Neutral**


TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are five different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Pre-attachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the SMark laser printer, PrintJet ADVANCED, plotter, MC-Mobilo or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-Ink or STI pen in connection with CLI T sleeves

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

**General ordering data**

|            |                            |   |
|------------|----------------------------|---|
| Type       | TM-I 23 MC NE RT           | Version                                 |
| Order No.  | <a href="#">1428510000</a> | TM-I, Insert markers, 23 x 4 mm, red    |
| GTIN (EAN) | 4050118232752              |   |
| Qty.       | 400 pc(s).                 |   |
| Type       | TM-I 23 MC NE WS           | Version                                 |
| Order No.  | <a href="#">1428480000</a> | TM-I, Insert markers, 23 x 4 mm, white  |
| GTIN (EAN) | 4050118232851              |   |
| Qty.       | 400 pc(s).                 |   |
| Type       | TM-I 23 MC NE BL           | Version                                 |
| Order No.  | <a href="#">1428520000</a> | TM-I, Insert markers, 23 x 4 mm, blue   |
| GTIN (EAN) | 4050118232875              |   |
| Qty.       | 400 pc(s).                 |   |
| Type       | TM-I 23 MC NE GE           | Version                                 |
| Order No.  | <a href="#">1428490000</a> | TM-I, Insert markers, 23 x 4 mm, yellow |
| GTIN (EAN) | 4050118232868              |   |
| Qty.       | 400 pc(s).                 |   |