SAISM-5/8S-M12 5P A-ZF



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com



Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly. Male plugs and female socket for customisable assembly for M8, M12, M16 and 7/8" connections which are highly robust and ideally suited to machine engineering, for instance. The M12 plug-in connectors offer a choice of 5 different connection systems.

e Ji-Ja

Tension-clamp connection delivers excellent functional security and reduced installation times. With this technology the conductor is plugged into the tension clamp without a wire-end ferrule (optionally with wireend ferrule). The connection between the conductor and tension clamp is vibration-resistant and boasts long-term stability.

General ordering data

Туре	SAISM-5/8S-M12 5P A-ZF		
Order No.	<u>1507700000</u>		
Version	Plugs prefabricated to customer spec., M12, pin, straight		
GTIN (EAN)	4050118316551		
Qty.	1 pc(s).		

SAISM-5/8S-M12 5P A-ZF

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Dimensions and weights			
Net weight	32 g		
Environmental Product Co	mpliance		
REACH SVHC	Lead 7439-92-1, Imidazolidine-2-thione 96-45-7		
Technical data customisab	le plug-in connectors		
Cable diameter, max.	8 mm	Cable diameter, min.	6 mm
Cable glands	PG 9	Coding	А
Connection cross-section, max.	0.75 mm ²	Connection cross-section, min.	0.14 mm ²
Contact surface	Gold-plated	Housing main material	CuZn
Number of poles	5	Pollution severity	3
Rated current	4 A	Rated voltage	125 V
Shield connection	Yes	Temperature range of housing	-40 +85 ° C
Threaded ring material	Diecast zinc	Type of connection	Tension-clamp connection
Classifications			
ETIM 6.0	EC002635	ETIM 7.0	EC002635
eClass 9.0	27-44-01-02	eClass 9.1	27-44-01-03
eClass 10.0	27-44-01-02		27 44 01 00
Approvals			
Approvals			
ROHS	Conform		
Downloads			
Brochure/Catalogue	FL FIELDWIRING EN		
,			