

**PAC**  
**PAC-YOKO-4X10-V0-10M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Similar to illustration

The pre-assembled PAC cables establish an electrical and logical connection between the PLC and the TERMSERIES relay modules. These cables consist of the following components:

- Manufacturer's PLC connector.
- Multi-pole LIYY cable with a cross-section of 0.14mm<sup>2</sup>.
- 10-pole flat cable connectors.

The cables are tested automatically for continuity and insulation to ensure the functionality for which they have been designed.

**General ordering data**

|            |  |
|------------|--|
| Type       | PAC-YOKO-4X10-V0-10M                             |
| Order No.  | <a href="#">1512190100</a>                       |
| Version    | Pre-assembled cable, PAC, Cable LiYY, 5.4 ± 1 mm |
| GTIN (EAN) | 4032248209484                                    |
| Qty.       | 1 pc(s).   |

Creation date May 4, 2020 2:23:27 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

## Data sheet

### PAC PAC-YOKO-4X10-V0-10M

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |         |
|------------|---------|
| Net weight | 1,648 g |
|------------|---------|

### Temperatures

|                             |             |                             |             |
|-----------------------------|-------------|-----------------------------|-------------|
| Operating temperature, max. | 50 °C       | Operating temperature, min. | -10 °C      |
| Storage temperature, max.   | 60 °C       | Storage temperature, min.   | -10 °C      |
| Operating temperature       | -10...50 °C | Storage temperature         | -10...60 °C |

### Environmental Product Compliance

|            |                |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

### General Data

|                       |            |                     |                      |
|-----------------------|------------|---------------------|----------------------|
| Connector PLC side    | HE10 50 P  | Interface connector | 4xHE10 10P           |
| Number of poles, min. | 10-pole    | Outer diameter      | 5.4 ± 1 mm           |
| Cable                 | Cable LiYY | Cable length        | 10 m                 |
| Material              | PVC        | Wire cross-section  | 0.14 mm <sup>2</sup> |

### Electrical Data

|                      |                     |   |           |
|----------------------|---------------------|---|-----------|
| Rated voltage (text) | ≤ 60 V DC ≤ 25 V AC | Permissible current strength per path, max. | 1 A       |
| Total current, max.  | 3 A                 | Resistance                                  | ≤ 150mΩ/m |
| High voltage test    | 1 KV/1s             |   |           |

### Classifications

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000237    | ETIM 7.0   | EC000237    |
| eClass 9.0  | 27-24-22-20 | eClass 9.1 | 27-24-22-20 |
| eClass 10.0 | 27-24-22-20 |            |             |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|