OMNIMATE Housing - series CH20M CH20M12 SET 1/2 BK/OR



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





Similar to illustration

Superior efficiency, flexibility and design - the "standard tailor-made fit"

When selecting a housing design, flexibility is a key factor. Other important criteria are: scalability, customized design, innovative functionality and cost efficiency. You need a choice which offers the maximum performance with the minimum overhead.

The CH20M12 modular electronics housing is the "small" option amongst the "large" housing solutions for compact electronics applications.

The entire system is characterized by excellence: outstanding scalability and flexibility, a high security level, innovative application functionality and a variety of practical details.

- Quicker installation with features such as "Wire ready" the universal multi-tool screw head
- User-friendly operations: with clear and permanent labelling and extra marking possibilities, integrated release clip or transparent cover
- Maximum interference immunity with EMCcompliant construction featuring deeply overlapping module joint edges made from high-performance plastic
- **High operational reliability** with the unique Auto-Set coding system and featuring double-sided touch protection on the pin header and socket blocks

CH20M - a compact name for the most flexible system available on the market. It doesn't just stand for "Component Housing IP20 Modular". CH20M also stands for efficiency and innovation throughout design, production and use.

General ordering data

Туре	CH20M12 SET 1/2 BK/OR
Order No.	<u>1519230000</u>
Version	Electronics housing sample, OMNIMATE Housing - series CH20M black, Sample kit for developers, consisting of individual parts incl. female plug, Width: 12.5 mm
GTIN (EAN)	4050118326987
Qty.	1 pc(s).

OMNIMATE Housing - series CH20M CH20M12 SET 1/2 BK/OR

Technical data



Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

· · · · ·			
Length	119.2 mm	Length (inches)	4.693 inch
Width	12.5 mm	Width (inches)	0.492 inch
Height	113.6 mm	Height (inches)	4.472 inch
Net weight	81 g		
System characteristics			
Version	Sample kit for developers, consisting of individual parts incl. female plug	Type of connection	pluggable
Number of connections	6	Number of connection levels	2
Number of PCBs per module	1	PCB thickness	1.6 mm
Type of contact to PCB	Solder connection, direct	Tolerance for the PCB shape	±0.1 mm
Contact to terminal rail	No	Encapsulation option	No
Material data			
	B		
Insulating material	PA 66 GF 30	Colour	black
Colour chart (similar)	RAL 9011	Insulating material group	
Comparative Tracking Index (CTI)	≥ 550	UL 94 flammability rating	V-0
Max. relative humidity during storage Operating temperature, max.	80 % 120 °C	Operating temperature, min.	-40 °C
	120 C		
Rated data acc. to IEC			
Rated current, max. number of poles	10 A	Rated current, max. number of poles (Tu=40°C)	9 A
(Tu=20°C)	1071		
(Tu=20°C) Rated voltage for surge voltage class / pollution degree II/2	400 V	Rated voltage for surge voltage class / pollution degree III/2	320 V
Rated voltage for surge voltage class /			
Rated voltage for surge voltage class / pollution degree II/2 Rated voltage for surge voltage class /	400 V 250 V	pollution degree III/2 Rated impulse voltage for surge voltage	4 kV
Rated voltage for surge voltage class / pollution degree II/2 Rated voltage for surge voltage class / pollution degree III/3 Rated impulse voltage for surge voltage	400 V 250 V	pollution degree III/2 Rated impulse voltage for surge voltage class/ pollution degree II/2 Rated impulse voltage for surge voltage	4 kV
Rated voltage for surge voltage class / pollution degree II/2 Rated voltage for surge voltage class / pollution degree III/3 Rated impulse voltage for surge voltage class/ pollution degree III/2 Classifications	400 V 250 V 4 kV	pollution degree III/2 Rated impulse voltage for surge voltage class/ pollution degree II/2 Rated impulse voltage for surge voltage class/ contamination degree III/3	4 kV 4 kV
Rated voltage for surge voltage class / pollution degree II/2 Rated voltage for surge voltage class / pollution degree III/3 Rated impulse voltage for surge voltage class/ pollution degree III/2 Classifications ETIM 6.0	400 V 250 V 4 kV EC001031	pollution degree III/2 Rated impulse voltage for surge voltage class/ pollution degree II/2 Rated impulse voltage for surge voltage class/ contamination degree III/3 ETIM 7.0	4 kV 4 kV EC001031
Rated voltage for surge voltage class / pollution degree II/2 Rated voltage for surge voltage class / pollution degree III/3 Rated impulse voltage for surge voltage class/ pollution degree III/2 Classifications ETIM 6.0 eClass 9.0	400 V 250 V 4 kV EC001031 27-18-27-02	pollution degree III/2 Rated impulse voltage for surge voltage class/ pollution degree II/2 Rated impulse voltage for surge voltage class/ contamination degree III/3	4 kV 4 kV
Rated voltage for surge voltage class / pollution degree II/2 Rated voltage for surge voltage class / pollution degree III/3 Rated impulse voltage for surge voltage class/ pollution degree III/2 Classifications ETIM 6.0 eClass 9.0	400 V 250 V 4 kV EC001031	pollution degree III/2 Rated impulse voltage for surge voltage class/ pollution degree II/2 Rated impulse voltage for surge voltage class/ contamination degree III/3 ETIM 7.0	4 kV 4 kV EC001031
Rated voltage for surge voltage class / pollution degree II/2 Rated voltage for surge voltage class / pollution degree III/3 Rated impulse voltage for surge voltage class/ pollution degree III/2 Classifications ETIM 6.0	400 V 250 V 4 kV EC001031 27-18-27-02	pollution degree III/2 Rated impulse voltage for surge voltage class/ pollution degree II/2 Rated impulse voltage for surge voltage class/ contamination degree III/3 ETIM 7.0	4 kV 4 kV EC001031
Rated voltage for surge voltage class / pollution degree II/2 Rated voltage for surge voltage class / pollution degree III/3 Rated impulse voltage for surge voltage class/ pollution degree III/3 Classifications ETIM 6.0 eClass 9.0 eClass 10.0	400 V 250 V 4 kV EC001031 27-18-27-02 27-18-27-02	pollution degree III/2 Rated impulse voltage for surge voltage class/ pollution degree II/2 Rated impulse voltage for surge voltage class/ contamination degree III/3 ETIM 7.0	4 kV 4 kV EC001031
Rated voltage for surge voltage class / pollution degree II/2 Rated voltage for surge voltage class / pollution degree III/3 Rated impulse voltage for surge voltage class/ pollution degree III/3 Rated impulse voltage for surge voltage class/ pollution degree III/2 Classifications ETIM 6.0 eClass 9.0 eClass 10.0 Approvals ROHS	400 V 250 V 4 kV EC001031 27-18-27-02	pollution degree III/2 Rated impulse voltage for surge voltage class/ pollution degree II/2 Rated impulse voltage for surge voltage class/ contamination degree III/3 ETIM 7.0	4 kV 4 kV EC001031
Rated voltage for surge voltage class / pollution degree II/2 Rated voltage for surge voltage class / pollution degree III/3 Rated impulse voltage for surge voltage class/ pollution degree III/3 Classifications ETIM 6.0 eClass 9.0 eClass 10.0	400 V 250 V 4 kV EC001031 27-18-27-02 27-18-27-02	pollution degree III/2 Rated impulse voltage for surge voltage class/ pollution degree II/2 Rated impulse voltage for surge voltage class/ contamination degree III/3 ETIM 7.0	4 kV 4 kV EC001031

Creation date May 4, 2020 2:03:06 AM CEST

OMNIMATE Housing - series CH20M CH20M12 SET 1/2 BK/OR

Drawings





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com