

**CAN SUB-D SK TERM**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Similar to illustration**

Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly.

**General ordering data**

Type	CAN SUB-D SK TERM
Order No.	<a href="#">1550580000</a>
Version	SUB-D
GTIN (EAN)	4050118357127
Qty.	1 pc(s).

## CAN SUB-D SK TERM

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

## Technical data

## Dimensions and weights

Width	46 mm	Width (inches)	1.811 inch
Height	54 mm	Height (inches)	2.126 inch
Depth	17 mm	Depth (inches)	0.669 inch
Net weight	96 g		

## Temperatures

Humidity	Max. 75% at +25°C, non-condensing
----------	-----------------------------------

## Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

## Technical specifications for sub-D connector

BUS interface	D-Sub 9-pole, Socket	BUS, cable interface	Screw connection
Data rate	1 Mbps	Housing main material	ZnAl
Humidity	Max. 75% at +25°C, non-condensing	Interlock	UNC4-40
Outgoing elbow	90°	Plugging cycles	≥ 200
Protection degree	IP30	Temperature range of housing	-20...+70 ° C
Terminating resistor available	Yes		

## Classifications

ETIM 6.0	EC001132	ETIM 7.0	EC001132
eClass 9.0	27-44-03-02	eClass 9.1	27-44-03-90
eClass 10.0	27-44-03-02		

## Approvals

ROHS	Conform
------	---------

## Downloads

Brochure/Catalogue	<a href="#">FL FIELDWIRING EN</a>
--------------------	-----------------------------------