

CAN SUB-D M12 TERM

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Similar to illustration

Individual cable lengths are often required nowadays. In order to meet these demands, Weidmüller offers a wide range of plug-in connectors for custom assembly.

General ordering data

Type	CAN SUB-D M12 TERM
Order No.	1555270000
Version	SUB-D
GTIN (EAN)	4050118361209
Qty.	1 pc(s).

Creation date May 4, 2020 12:48:10 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

CAN SUB-D M12 TERM

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Dimensions and weights

Width	46.5 mm	Width (inches)	1.831 inch
Height	59 mm	Height (inches)	2.323 inch
Depth	16.8 mm	Depth (inches)	0.661 inch
Net weight	90 g		

Temperatures

Humidity	Max. 75% at +25°C, non-condensing
----------	-----------------------------------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Technical specifications for sub-D connector

BUS interface	D-Sub 9-pole, Socket	BUS, cable interface	M12 A-coded, pin + socket
Data rate	1 Mbps	Housing main material	ZnAl
Humidity	Max. 75% at +25°C, non-condensing	Interlock	UNC4-40
Outgoing elbow	90°	Plugging cycles	≥ 200
Protection degree	IP30	Temperature range of housing	-20...+70 ° C
Terminating resistor available	Yes		

Classifications

ETIM 6.0	EC001132	ETIM 7.0	EC001132
eClass 9.0	27-44-03-02	eClass 9.1	27-44-03-90
eClass 10.0	27-44-03-02		

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	FL FIELDWIRING EN
--------------------	-----------------------------------