

CableLine
CLI C 2-4 SW/WS 0 CD

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



CLI C conductor markers are mounted on unconnected conductors. Four different sizes are available for labelling conductor cross-sections from 0.5 mm² to max. 70 mm². The markers are already printed and ready for use. Individual labelling is possible by combining the individual markers.

- Closed markers, reliable and for mounting on unconnected cables
- A special flexible bellow profile ensures a wide application range
- Fast and easy to fit – with minimal effort
- Corresponding accessories make labelling easy
- Permanent, high-quality labelling
- High contrast for optimum legibility

General ordering data

| | |
|------------|--|
| Type | CLI C 2-4 SW/WS 0 CD |
| Order No. | 1568261503 |
| Version | CableLine, Conductor and cable markers, 4 - 10 mm, 4 x 7 mm, black |
| GTIN (EAN) | 4008 1909 16183 |
| Qty. | 250 pc(s). |

**CableLine
CLI C 2-4 SW/WS 0 CD**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

| | | | |
|------------|-------|-----------------|------------|
| Width | 7 mm | Width (inches) | 0.276 inch |
| Height | 4 mm | Height (inches) | 0.157 inch |
| Depth | 8 mm | Depth (inches) | 0.315 inch |
| Net weight | 0.2 g | | |

General data

| | | | |
|-----------------------------|----------------------------|--|--------------------|
| Colour | black | Colour of printing | white |
| Halogen | Yes | Insulation cross-section, max. | 10 mm |
| Material | PVC, soft, without Cadmium | Material colour according to resistance code | 0 |
| Operating temperature range | -30...80 °C | Orientation of print | horizontal |
| Printed characters | Numbers | Printing | 0 |
| Printing method | hot-embossing | Recommended industries | Process, Machinery |
| Type of printing | Standard | UL 94 flammability rating | V-0 |
| Version | CD | Width | 7 mm |

Conductor and cable markers

| | | | |
|-------------------------------|---------------------|-------------------------------|--------------------|
| Conductor O.D. | 4 - 10 mm | Conductor O.D., max. | 10 mm |
| Conductor O.D., min. | 4 mm | Conductor cross-section, max. | 16 mm ² |
| Conductor cross-section, min. | 2.5 mm ² | Halogen | Yes |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| eClass 9.0 | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 | UNSPSC | 44-12-17-08 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|-----------------------------|--|
| Engineering Data | EPLAN, WSCAD |
| Product Change Notification | PCN CableLine_DE PCN CableLine_EN |