

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

HDC 16B TSLU 1PG21G
<u>1657850000</u>
HDC enclosures, Size: 6, Protection degree: IP65, Cable entry from side, Plug housing, End-locking clamp, lower side, Standard, Size of cable entries: PG 21
4008190410902
1 pc(s).

Technical data



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Width	45.5 mm	Width (inches)	1.791 inch
Height	61 mm	Height (inches)	2.402 inch
Net weight	226 g		
Temperatures			
Limit temperature	-40 °C 125 °C		
Environmental Product Co	mpliance		
REACH SVHC	Lead 7439-92-1		
Dimensions			
Cable antes		Unight of hereign D	61
Cable entry	w. threading 93.3 mm	Height of housing B Width housing C	61 mm 43 mm
Total length housing	93.3 mm	Width housing C	43 mm
General data			
EMC housings	No	Housing main material	diecast aluminium
Material of locking element	Stainless steel, rust-proof	Protection degree	IP65
Surface finish	Powder coating	Tightening torque	1.2 Nm
Version			
Cable entry	w. threading	Clamp version	End-locking clamp
Design	w. threading	Design of housing	Cable entry from side, Plu
200.91	Standard	2 congin en nie dennig	housing
Design of locking system	End-locking clamp, lower side	Internal thread	PG 21
Number of cable entry on top	0	Number of cable entry sideways	1
Size	6	Size of cable entries	PG 21
Suitable for ModuPlug [®]	No	Tightening torque	1.2 Nm
Top part/bottom part/lid	upper part	Туре	Plug
Classifications			
ETIM 6.0	EC000437	ETIM 7.0	EC000437
eClass 9.0	27-44-02-02	eClass 9.1	27-44-02-02
eClass 10.0	27-44-02-02	UNSPSC	30-21-18-01
Approvals			
Approvals	(E P	- 30 	

ROHS

Conform

Technical data

Downloads




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Brochure/Catalogue	<u>CAT 3 HDC 17/18 EN</u>
	FL FIELDWIRING EN
Engineering Data	EPLAN, WSCAD
Engineering Data	<u>STEP</u>
Technical Documentation	1657850000_HDC_16B_TSLU_1PG21G_STP_Blatt1.pdf

Drawings





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Base housing





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

General	oracing aata	
Туре	HDC 40D SDLU 1PG29G	Version
Order No.	<u>1658410000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4008190411459	locking clamp, lower side, high, with cover, Size of cable entries: PG
Qty.	1 pc(s).	29
Туре	HDC 16B SLU 2PG21G	Version
Order No.	<u>1658120000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4008190411176	locking clamp, lower side, Standard, Size of cable entries: PG 21
Qty.	1 pc(s).	
Туре	HDC 40D SDLU 1M25G	Version
Order No.	<u>1903070000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4032248592975	locking clamp, lower side, high, with cover, Size of cable entries: M 25
Qty.	1 pc(s).	
Туре	HDC 16B SDLU 2PG21G	Version
Order No.	<u>1658330000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4008190411381	locking clamp, lower side, Standard, with cover, Size of cable entries:
Qty.	1 pc(s).	PG 21
Туре	HDC 40D SDLU 1M32G	Version
Order No.	<u>1903080000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4032248592982	locking clamp, lower side, high, with cover, Size of cable entries: M 32
Qty.	1 pc(s).	
Туре	HDC 16B SLU 1M25G	Version
Order No.	<u>1900170000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4032248520800	locking clamp, lower side, Standard, Size of cable entries: M 25
Qty.	1 pc(s).	
Туре	HDC 16B SLU 2M25G	Version
Order No.	<u>1788250000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4032248205783	locking clamp, lower side, Standard, Size of cable entries: M 25
Qty.	1 pc(s).	
Туре	HDC 16B SDLU 1M25G	Version
Order No.	<u>1415810000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4050118217230	locking clamp, lower side, Standard, with cover, Size of cable entries:
Qty.	1 pc(s).	M 25

Creation date May 3, 2020 3:34:09 PM CEST

Accessories



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Туре	HDC 40D SLU 2M32G	Version
Order No.	<u>1804660000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4032248267606	locking clamp, lower side, high, Size of cable entries: M 32
Qty.	1 pc(s).	
Туре	HDC 40D SLU 1M32G	Version
Order No.	<u>1903110000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4032248590117	locking clamp, lower side, high, Size of cable entries: M 32
Qty.	1 pc(s).	
Туре	HDC 16B SDLU 2M25G	Version
Order No.	<u>1788270000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4032248205806	locking clamp, lower side, Standard, with cover, Size of cable entries:
Qty.	1 pc(s).	M 25
Туре	HDC 16B SLU 1PG21G	Version
Order No.	<u>1658110000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4008190411169	locking clamp, lower side, Standard, Size of cable entries: PG 21
Qty.	1 pc(s).	
Туре	HDC 40D SDLU 2M32G	Version
Order No.	<u>1787170000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4032248204519	locking clamp, lower side, high, with cover, Size of cable entries: M 32
Qty.	1 pc(s).	
Туре	HDC 16B SDLU 1PG21G	Version
Order No.	<u>1658320000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4008190411374	locking clamp, lower side, Standard, with cover, Size of cable entries:
Qty.	1 pc(s).	PG 21
Туре	HDC 40D SDLU 2M25G	Version
Order No.	<u>1787180000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, End-
GTIN (EAN)	4032248204526	locking clamp, lower side, high, with cover, Size of cable entries: M 25
Qty.	1 pc(s).	

Bulkhead housing



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 16B ADLU	Version
Order No.	<u>1210100000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Open base, End-
GTIN (EAN)	4008190050924	locking clamp, lower side, Standard, with cover
Qty.	1 pc(s).	

Creation date May 3, 2020 3:34:09 PM CEST

Accessories

v	erc	Im	UII	er	

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Туре	HDC 16B ALU	Version
Order No.	<u>1209700000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Open base, End-
GTIN (EAN)	4008190000134	locking clamp, lower side, Standard
Qty.	1 pc(s).	

Coupling hood



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 16B KLU 1M25G	Version
Order No.	<u>1788290000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed housing, End-
GTIN (EAN)	4032248205820	locking clamp, lower side, Standard, Size of cable entries: M 25
Qty.	1 pc(s).	
Туре	HDC 40D KLU 1M25G	Version
Type Order No.	HDC 40D KLU 1M25G 1787220000	Version HDC enclosures, Size: 6, Protection degree: IP65, Closed housing, End-