

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com







The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 32A SBU 1PG29G
Order No.	<u>1666010000</u>
Version	HDC enclosures, Size: 7, Protection degree: IP65,
	Closed base, Side-locking clamp on lower side,
	Standard, Size of cable entries: PG 29
GTIN (EAN)	4008190423049
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Width	68 mm	Width (inches)	2.677 inch
Height	75 mm	Height (inches)	2.953 inch
Mounting dimension - width	92 mm	Mounting dimension - height	46 mm
Net weight	441 g		

Temperatures

Limit temperature -40 °C ... 125 °C

Environmental Product Compliance

REACH SVHC Lead 7439-92-1, DIBP

84-69-5, Potassium perfluorobutane sulfonate 29420-49-3

Dimensions

Cable entry	w. threading	Height of base B1	5 mm
Height of housing B	75 mm	Hole pitch length A2	92 mm
Total length housing	82 mm	Width base C1	64.5 mm
Width housing C	56 mm		

General data

EMC housings	No	Housing main material	diecast aluminium
Material of locking element	Stainless steel, rust-proof	Protection degree	IP65
Surface finish	Powder coating	Tightening torque	1.2 Nm

Version

Coble ontry	us throughns	Clampyoroian	Cida laaking alamn
Cable entry	w. threading	Clamp version	Side-locking clamp
Design	Standard	Design of housing	Closed base
Design of locking system	Side-locking clamp on	Internal thread	
	lower side		PG 29
Number of cable entry on top	0	Number of cable entry sideways	1
Sealing	NBR	Size	7
Size of cable entries	PG 29	Suitable for ModuPlug [®]	No
Tightening torque	1.2 Nm	Top part/bottom part/lid	lower part
Туре	Base housing		

Classifications

ETIM 6.0	EC000437	ETIM 7.0	EC000437
eClass 9.0	27-44-02-02	eClass 9.1	27-44-02-02
eClass 10.0	27-44-02-02	UNSPSC	30-21-18-01

Approvals

Approvals





Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Downloads

Brochure/Catalogue	CAT 3 HDC 17/18 EN
	<u>FL FIELDWIRING EN</u>
Engineering Data	EPLAN, WSCAD
Engineering Data	<u>STEP</u>
Product Change Notification	DE - HDC base housings size 16D/32A/32B
	DE - HDC base housings size 16D/32A/32B
Technical Documentation	1666010000_HDC_32A_SBU_1PG29G_STP_Blatt1.pdf




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Drawings





Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Cover



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

	-	
Туре	HDC 32A DODQ 4BO	Version
Order No.	<u>1665920000</u>	HDC enclosures, Size: 7, Protection degree: IP65, Cover for lower part
GTIN (EAN)	4008190422950	of housing, Side-locking clamp on lower side, Standard
Qty.	1 pc(s).	

Hood, Cable Entry at top



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 32A TOBU 1PG29G	Version
Order No.	<u>1665810000</u>	HDC enclosures, Size: 7, Protection degree: IP65, Cable entry from
GTIN (EAN)	4008190422837	top, Plug housing, Side-locking clamp on lower side, Standard, Size of
Qty.	1 pc(s).	cable entries: PG 29
Туре	HDC 32A TOBU 1PG21G	Version
Type Order No.	HDC 32A TOBU 1PG21G 1665790000	Version HDC enclosures, Size: 7, Protection degree: IP65, Cable entry from

Creation date May 3, 2020 3:02:07 PM CEST



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Туре	HDC 32A TOBU 1M32G	Version
Order No.	<u>1787990000</u>	HDC enclosures, Size: 7, Protection degree: IP65, Cable entry from
GTIN (EAN)	4032248205431	top, Plug housing, Side-locking clamp on lower side, Standard, Size of
Qty.	1 pc(s).	cable entries: M 32

Hood, Cable Entry sideways



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

General ordering data

Туре	HDC 32A TSBU 1PG29G	Version
Order No.	<u>1665690000</u>	HDC enclosures, Size: 7, Protection degree: IP65, Cable entry from
GTIN (EAN)	4008190422714	side, Plug housing, Side-locking clamp on lower side, Standard, Size of
Qty.	1 pc(s).	cable entries: PG 29
Туре	HDC 32A TSBU 1PG21G	Version
Order No.	<u>1665670000</u>	HDC enclosures, Size: 7, Protection degree: IP65, Cable entry from
GTIN (EAN)	4008190422691	side, Plug housing, Side-locking clamp on lower side, Standard, Size of
Qty.	1 pc(s).	cable entries: PG 21
Туре	HDC 32A TSBU 1M25G	Version
Type Order No.	HDC 32A TSBU 1M25G 1787960000	Version HDC enclosures, Size: 7, Protection degree: IP65, Cable entry from
Order No.	<u>1787960000</u>	HDC enclosures, Size: 7, Protection degree: IP65, Cable entry from
Order No. GTIN (EAN)	1787960000 4032248205400	HDC enclosures, Size: 7, Protection degree: IP65, Cable entry from side, Plug housing, Side-locking clamp on lower side, Standard, Size of
Order No. GTIN (EAN) Qty.	1787960000 4032248205400 1 pc(s).	HDC enclosures, Size: 7, Protection degree: IP65, Cable entry from side, Plug housing, Side-locking clamp on lower side, Standard, Size of cable entries: M 25
Order No. GTIN (EAN) Oty. Type	1787960000 4032248205400 1 pc(s). HDC 32A TSBU 1M32G	HDC enclosures, Size: 7, Protection degree: IP65, Cable entry from side, Plug housing, Side-locking clamp on lower side, Standard, Size of cable entries: M 25 Version