

**LaserMark  
LM WO 25/68 GE**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



Similar to illustration



LM WriteOn cable markers on DIN A4 sheets are used for labelling conductors and cables up to an outside diameter of 36 mm. The transparent adhesive strip fixes and protects the printing on the marker surface.

- Protection of the marking against dirt and abrasion by wrapping it with the transparent adhesive strip
- Easy and quick labelling with a DIN A4 laser printer or STI pen

**General ordering data**

|            |   |
|------------|---|
| Type       | LM WO 25/68 GE  |
| Order No.  | <a href="#">1695731687</a>  |
| Version    | LaserMark, Conductor and cable markers, 8.2 - 14.3 mm, 25 x 68 mm, yellow |
| GTIN (EAN) | 4008 190924713  |
| Qty.       | 10 pc(s).   |

## Data sheet

### LaserMark LM WO 25/68 GE

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Width      | 68 mm    | Width (inches)  | 2.677 inch |
| Height     | 25 mm    | Height (inches) | 0.984 inch |
| Depth      | 0.025 mm | Depth (inches)  | 0.001 inch |
| Net weight | 10.2 g   |                 |            |

### General data

|  |            |                                      |                |
|--|------------|--------------------------------------|----------------|
| Adhesive                                     | Acrylate   | Colour                               | yellow         |
| Halogen                                      | No         | Material                             | Polyester film |
| Material colour according to resistance code | 4          | Number of markers per packaging unit | 280            |
| Number per sheet                             | 28         | Operating temperature range          | -40... 150 °C  |
| Size of labelling field                      | 25 x 17 mm | Type of printing                     | neutral        |
| UL 94 flammability rating                    | V-0        | Version                              | Self-adhesive  |
| Width  | 68 mm      |                                      |                |

### Conductor and cable markers

|                               |                    |                               |                    |
|-------------------------------|--------------------|-------------------------------|--------------------|
| Conductor O.D.                | 8.2 - 14.3 mm      | Conductor O.D., max.          | 14.3 mm            |
| Conductor O.D., min.          | 8.2 mm             | Conductor cross-section, max. | 70 mm <sup>2</sup> |
| Conductor cross-section, min. | 16 mm <sup>2</sup> | Halogen                       | No                 |

### Classifications

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0   | EC001530    |
| eClass 9.0  | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 | UNSPSC     | 44-12-17-08 |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                  |  |
|------------------|--|
| Engineering Data | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>       |
| Engineering Data | <a href="#">STEP</a>                           |
| Software         | <a href="#">M-Print PRO configuration file</a> |

**Data sheet**

**LaserMark  
LM WO 25/68 GE**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

