

SlimFix VT SF 3/12 MC NE BL V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Similar to illustration



SlimFix are conductor and cable markers with a space-saving design. The markers can be fitted even after the conductor has been installed. They consist of halogen-free material and comply with flammability rating V0/V2. SlimFix is an acknowledged and accredited marker type for traffic engineering applications. The SF tool allows easy installation, even in case of small markers.

- Halogen-free material
- Flammability rating V0/V2
- Approved and accredited markers for traffic engineering applications, etc.
- Has to be fixed with cable ties if the conductor cross-section is larger than 16.0 mm²
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| | |
|--------------------|--|
| Type | VT SF 3/12 MC NE BL V0 |
| Order No. | 1718490002 |
| Version | SlimFix, Conductor and cable markers, 3 - 3.7 mm, 12 x 4.6 mm, blue |
| GTIN (EAN) | 4008190349615 |
| Qty. | 640 pc(s). |
| compatible printer | 1324380000 2438520000 2438510000 |

SlimFix
VT SF 3/12 MC NE BL V0

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|------------|---------|-----------------|------------|
| Width | 4.6 mm | Width (inches) | 0.181 inch |
| Height | 12 mm | Height (inches) | 0.472 inch |
| Depth | 4.8 mm | Depth (inches) | 0.189 inch |
| Net weight | 0.303 g | | |

General data

| | | | |
|-----------------------------|--------------|--|---------------------------|
| Colour | blue | Halogen | No |
| Material | Polyamide 66 | Material colour according to resistance code | 6 |
| Operating temperature range | -50...120 °C | Recommended industries | Transportation, Machinery |
| Size of labelling field | 12 x 4.6 mm | Type of printing | neutral |
| UL 94 flammability rating | V-0 | Width | 4.6 mm |

Conductor and cable markers

| | | | |
|-------------------------------|---------------------|-------------------------------|---------------------|
| Conductor O.D. | 3 - 3.7 mm | Conductor O.D., max. | 3.7 mm |
| Conductor O.D., min. | 3 mm | Conductor cross-section, max. | 2.5 mm ² |
| Conductor cross-section, min. | 1.5 mm ² | Halogen | No |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| eClass 9.0 | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 | UNSPSC | 44-12-17-08 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|--|
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Engineering Data | STEP |
| Software | M-Print PRO configuration file |

Data sheet

SlimFix
VT SF 3/12 MC NE BL V0

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

