

**CableLine  
CLI T 2-15**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



Similar to illustration

The CLI T sleeve is a high-quality, transparent sleeve for marking conductors and cables with cross-sections up to 75 mm<sup>2</sup>. The CLI T sleeve is available in four lengths so that labelling with long character strings is possible. The transparent sleeve optimally protects the inlay tag against outside influences. As inlay tag the TM-I marker from the MultiCard portfolio be suitable. The CLI T sleeves should not be used together with the MultiMark TM-I inlay tag. We are currently working on an optimal usability of the TM-I tag from the MultiMark series.

- Wider cross-section range per sleeve
- A special flexible bellow profile ensures a wide application range
- Easy insertion of the TM-I tag into the sleeve pocket before or after connecting the conductor
- Available in five lengths
- Not suitable for labelling with P-Ink or STI pen

**General ordering data**

|            |   |
|------------|---|
| Type       | CLI T 2-15  |
| Order No.  | <a href="#">1764240000</a>  |
| Version    | CableLine, Socket x 5 mm, PVC, Colour: Transparent, Conductor O.D.: 4 - 10 mm |
| GTIN (EAN) | 4032248053308   |
| Qty.       | 100 pc(s).  |

**CableLine  
CLIT 2-15**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |        |                 |            |
|------------|--------|-----------------|------------|
| Width      | 5 mm   | Width (inches)  | 0.197 inch |
| Height     | 15 mm  | Height (inches) | 0.591 inch |
| Depth      | 13 mm  | Depth (inches)  | 0.512 inch |
| Net weight | 0.51 g |                 |            |

**General data**

|                        |                           |                             |             |
|------------------------|---------------------------|-----------------------------|-------------|
| Colour                 | Transparent               | Halogen                     | Yes         |
| Material               | PVC                       | Operating temperature range | -30...80 °C |
| Recommended industries | Transportation, Machinery | Type of printing            | neutral     |
| Width                  | 5 mm                      |                             |             |

**Conductor and cable markers**

|                               |                   |                               |                    |
|-------------------------------|-------------------|-------------------------------|--------------------|
| Conductor O.D.                | 4 - 10 mm         | Conductor O.D., max.          | 10 mm              |
| Conductor O.D., min.          | 4 mm              | Conductor cross-section, max. | 35 mm <sup>2</sup> |
| Conductor cross-section, min. | 4 mm <sup>2</sup> | Halogen                       | Yes                |

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0   | EC001530    |
| eClass 9.0  | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 | UNSPSC     | 44-12-17-08 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                             |  |
|-----------------------------|--|
| Engineering Data            | <a href="#">EPLAN, WSCAD</a>   |
| Product Change Notification | <a href="#">PCN Transparent Sleeves_DE</a><br><a href="#">PCN Transparent Sleeves_EN</a> |