

**SKMU PA (plastic locknut)
SKMU M12 - K GR**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Weidmüller has a variety of different cable and wire entry systems in the Portfolio: with different designs of plastic, brass and stainless steel cable glands in the IP66, 67, 68 or IP69k protection classes. As a complete alternative to cable glands, pre-assembled cables with modular multi-wire or multi-cable entry systems can be simply and quickly inserted into electrical equipment. Last but not least, Weidmüller offers EX-certified cable glands and cable/wire entry systems.

- Cable glands made from plastic and brass
- EMC screwed joints
- for areas at risk of explosion
- VDE, CSA and UL approvals

General ordering data

| | |
|------------|---|
| Type | SKMU M12 - K GR |
| Order No. | 1772440000 |
| Version | SKMU PA (plastic locknut), Locknut, M 12, 5 mm, Polyamid 6 (PA6 - GF30) |
| GTIN (EAN) | 4032248130184 |
| Qty. | 100 pc(s). |

SKMU PA (plastic locknut) SKMU M12 - K GR

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight 0.9 g

General information

| | | | |
|-----------------------------------|-------------------------|-----------------------------------|--------|
| Material | Polyamid 6 (PA6 - GF30) | Cable glands | metric |
| External thread | M 12 | Pitch of thread | 1.5 mm |
| Length of thread | 5 mm | AF size 1 | 18 mm |
| Operating temperature range, min. | -40 °C | Operating temperature range, max. | 100 °C |
| Thickness | 5 mm | UL 94 flammability rating | V-2 |
| Internal thread | M 12 x 1.5 | Halogen | No |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC000940 | ETIM 7.0 | EC000940 |
| eClass 9.0 | 27-14-44-24 | eClass 9.1 | 27-14-44-24 |
| eClass 10.0 | 27-14-44-24 | UNSPSC | 30-21-18-01 |

Approvals

Approvals



ROHS Conform

Downloads

| | |
|--------------------|-------------------------------------|
| Brochure/Catalogue | CAT 5 ENCL 17/18 EN |
| Engineering Data | EPLAN, WSCAD |
| Engineering Data | STEP |

Data sheet

**SKMU PA (plastic locknut)
SKMU M12 - K GR**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

