

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com









The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

#### General ordering data

Туре	HDC 40D TSBU 1M32G
Order No.	<u>1787000000</u>
Version	HDC enclosures, Size: 6, Protection degree: IP65, Cable entry from side, Plug housing, Side-locking clamp on lower side, high, Size of cable entries: M 32
GTIN (EAN)	4032248204243
Oty.	1 pc(s).



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Technical data**

#### **Dimensions and weights**

Width	59 mm	Width (inches)	2.323 inch
Height	76 mm	Height (inches)	2.992 inch
Depth	93.3 mm	Depth (inches)	3.673 inch
Net weight	269.5 g		

#### **Temperatures**

Limit temperature -40 °C ... 125 °C

#### **Environmental Product Compliance**

REACH SVHC Lead 7439-92-1

#### **Dimensions**

Cable entry	w. threading	Height of housing B	76 mm	
Total length housing	93.3 mm	Width housing C	43 mm	

#### **General data**

EMC housings	No	Housing main material	diecast aluminium
Material of locking element	Stainless steel, rust-proof	Protection degree	IP65
Surface finish	Powder coating	Tightening torque	1.2 Nm

#### Version

Cable entry	w. threading	Clamp version	Side-locking clamp
Design	high	Design of housing	Cable entry from side, Plug housing
Design of locking system	Side-locking clamp on	Internal thread	
	lower side		M 32
Number of cable entry on top	0	Number of cable entry sideways	1
Size	6	Size of cable entries	M 32
Suitable for ModuPlug <sup>®</sup>	Yes	Tightening torque	1.2 Nm
Top part/bottom part/lid	upper part	Туре	Plug

#### **Classifications**

ETIM 6.0	EC000437	ETIM 7.0	EC000437
eClass 9.0	27-44-02-02	eClass 9.1	27-44-02-02
eClass 10.0	27-44-02-02	UNSPSC	30-21-18-01

#### **Approvals**

Approvals



ROHS Conform



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Technical data**

#### **Downloads**

Brochure/Catalogue	CAT 3 HDC 17/18 EN
	FL FIELDWIRING EN
Engineering Data	EPLAN, WSCAD, Zuken E3.S
Engineering Data	<u>STEP</u>
Technical Documentation	1787000000_HDC_40D_TSBU_1M32G_STP_Blatt1.pdf




Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Drawings**





## Accessories

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

#### Cover



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

#### **General ordering data**

Type HDC 16B DMDQ 2QB Version

Order No. 1665270000 HDC enclosures, Size: 6, Protection degree: IP65, Cover for upper part of housing, Side-locking clamp on lower side, Standard Qty. 1 pc(s).

#### Coupling hood



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

#### General ordering data

Туре	HDC 40D KBU 1M25G N	Version
Order No.	<u>2559890000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed housing,
GTIN (EAN)	4050118676440	Side-locking clamp on lower side, high, Size of cable entries: PG 29
Qty.	1 pc(s).	
Туре	HDC 40D KBU 1M32G	Version
Type Order No.	HDC 40D KBU 1M32G 1787190000	Version HDC enclosures, Size: 6, Protection degree: IP65, Closed housing,

Creation date May 3, 2020 2:34:16 PM CEST



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083

www.weidmueller.com

### **Accessories**

Туре	HDC 40D KBU 1PG21G	Version
Order No.	1657310000	HDC enclosures, Size: 6, Protection degree: IP65, Closed housing,
GTIN (EAN)	4008190410360	Side-locking clamp on lower side, high, Size of cable entries: PG 21
Qty.	1 pc(s).	
Туре	HDC 40D KBU 1PG29G	Version
Order No.	<u>1967670000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed housing,
GTIN (EAN)	4032248670178	Side-locking clamp on lower side, high, Size of cable entries: PG 29
Qty.	1 pc(s).	
Туре	HDC 16B KBU 1PG21G	Version
Order No.	1657270000	HDC enclosures, Size: 6, Protection degree: IP65, Closed housing,
GTIN (EAN)	4008190410322	Side-locking clamp on lower side, Standard, Size of cable entries: PG
Qty.	1 pc(s).	21
Туре	HDC 40D KBU 1M25G	Version
Order No.	<u>1787200000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed housing,
GTIN (EAN)	4032248204540	Side-locking clamp on lower side, high, Size of cable entries: M 25
Qty.	1 pc(s).	
Туре	HDC 40D KBU 2M32G N	Version
Order No.	<u>2545510000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed housing,
GTIN (EAN)	4050118558333	Side-locking clamp on lower side, high, Size of cable entries: PG 29
Qty.	1 pc(s).	
Туре	HDC 40D KBU 1M32G N	Version
Order No.	<u>2559900000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed housing,
GTIN (EAN)	4050118673265	Side-locking clamp on lower side, high, Size of cable entries: PG 29
Qty.	1 pc(s).	

#### **Base housing**



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

#### **General ordering data**

Туре	HDC 40D SBU 1M25G	Version
Order No.	<u>1902970000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4032248592951	locking clamp on lower side, high, Size of cable entries: M 25
Qty.	1 pc(s).	
Туре	HDC 40D SBU 2M25G N	Version
Type Order No.	HDC 40D SBU 2M25G N 2561020000	Version HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-

Creation date May 3, 2020 2:34:16 PM CEST



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## Accessories

Туре	HDC 16B SBU 1PG21G	Version
Order No.	<u>1656720000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4008190409739	locking clamp on lower side, Standard, Size of cable entries: PG 21
Qty.	1 pc(s).	
Туре	HDC 16B SBU 1M25G N	Version
Order No.	<u>2560740000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4050118673234	locking clamp on lower side, Standard, Size of cable entries: M 25
Qty.	1 pc(s).	
Туре	HDC 16B SBU 2M25G N	Version
Order No.	2560930000	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4050118673531	locking clamp on lower side, Standard, Size of cable entries: M 25
Qty.	1 pc(s).	
Type	HDC 40D SBU 2PG29G	Version
Order No.	1656840000	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4008190409852	locking clamp on lower side, high, Size of cable entries: PG 29
		locking clamp of lower side, high, size of cable entities. FG 25
Qty.	1 pc(s).	v ·
Туре	HDC 40D SBU 1M32G	Version
Order No.	1902990000	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4032248592968	locking clamp on lower side, high, Size of cable entries: M 32
Qty.	1 pc(s).	
Туре	HDC 40D SBU 2PG21G	Version
Order No.	<u>1656810000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4008190409821	locking clamp on lower side, high, Size of cable entries: PG 21
Qty.	1 pc(s).	
Туре	HDC 40D SBU 2M25G	Version
Order No.	<u>1787120000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4032248204465	locking clamp on lower side, high, Size of cable entries: M 25
Qty.	1 pc(s).	
Туре	HDC 40D SBU 2M32G	Version
Order No.	<u>1787110000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4032248204458	locking clamp on lower side, high, Size of cable entries: M 32
Qty.	1 pc(s).	
Type	HDC 16B SBU 2M25G	Version
Order No.	1788240000	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4032248205776	locking clamp on lower side, Standard, Size of cable entries: M 25
Qty.	1 pc(s).	looking dump of lower due, dumulu, oles of duble offices. W 25
		Varian
Type Order No.	HDC 40D SBU 1PG29G 1656830000	Version  HDC anclosures Size: 6 Protection degree: IB65 Closed has a Side.
		HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4008190409845	locking clamp on lower side, high, Size of cable entries: PG 29
Qty.	1 pc(s).	
Туре	HDC 40D SBU 1PG29G N	Version
Order No.	<u>2560770000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)		locking clamp on lower side, high, Size of cable entries: PG 21
Qty.	1 pc(s).	
Туре	HDC 40D SBU 2M32G N	Version
Order No.	<u>2561040000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4050118676457	locking clamp on lower side, high, Size of cable entries: PG 21
Qty.	1 pc(s).	
Туре	HDC 40D SBU 1M32G N	Version
Order No.	<u>2561030000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4050118676464	locking clamp on lower side, high, Size of cable entries: PG 21
Qty.	1 pc(s).	



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### **Accessories**

Туре	HDC 16B SBU 1M25G	Version
Order No.	1899980000	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4032248520718	locking clamp on lower side, Standard, Size of cable entries: M 25
Qty.	1 pc(s).	
Туре	HDC 16B SBU 2PG21G N	Version
Order No.	<u>2560950000</u>	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
GTIN (EAN)	4050118676921	locking clamp on lower side, Standard, Size of cable entries: PG 21
Qty.	1 pc(s).	
Туре	HDC 16B SBU 1PG21G N	Version
Type Order No.	HDC 16B SBU 1PG21G N 2560940000	Version HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
• •		
Order No.	2560940000	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
Order No. GTIN (EAN)	<u>2560940000</u> 4050118676716	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-
Order No. GTIN (EAN) Oty.	2560940000 4050118676716 1 pc(s).	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side- locking clamp on lower side, Standard, Size of cable entries: PG 21
Order No. GTIN (EAN) Oty. Type	2560940000 4050118676716 1 pc(s). HDC 16B SBU 2PG21G	HDC enclosures, Size: 6, Protection degree: IP65, Closed base, Side-locking clamp on lower side, Standard, Size of cable entries: PG 21  Version

#### **Bulkhead housing**



The special die-cast alloy and the multi-layered surface sealing provide complete protection for the HDC housings.

The cleverly designed interlock system is manufactured from stainless steel. This guarantees a long lifespan with high resistance to corrosion and impact.

The housing interlock system provides integrated safety. Our unique, patented spring system provides the housing interlock with a secure grip and prevents accidental opening.

The laser marking allows for easy and quick identification. Each housing is permanently labelled with a laser marking so that each product can be quickly designated and positioned.

Weidmüller RockStar® IP 65 / NEMA Type 4X housings - your first choice for industrial housings with IP 65 protection.

#### **General ordering data**

Туре	HDC 16B ABU	Version
Order No.	1208600000	HDC enclosures, Size: 6, Protection degree: IP65, Open base, Side-
GTIN (EAN)	4008190881351	locking clamp on lower side, Standard
Qty.	1 pc(s).	
Туре	HDC 16B ABU N	Version
Type Order No.	HDC 16B ABU N 2488590000	Version HDC enclosures, Size: 6, Protection degree: IP65, Open base, Side-
• •		