

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com











Sensor/actuator cables are used for wiring sensors and actuators and for transmitting data or power in various applications. The moulded cable offers connected and tested connection of the plug-in connector to the cable ex-works. The cables may be exposed to a wide range of conditions, such as humidity, dust, heat, cold, shock or vibration

Our developers have focused specifically on this issue and designed a host of different M8 and M12 sensor-actuator cables so you are bound to find the solution you need for your application.

Is there something you have not managed to find or you feel needs explanation? Talk to us!

General ordering data

Туре	SAIL-M8BGR-3-10V
Order No.	<u>1948711000</u>
Version	Sensor/actuator line, One end without connector, M12 / M8, Number of poles: 3, 10 m, Female socket, straight, Shielded: No, LED: No, Sheath material: PVC, Halogen: Yes
GTIN (EAN)	4032248626007
Qty.	1 pc(s).

Creation date May 3, 2020 8:48:14 AM CEST



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Net weight	100 g

Temperatures

Operating temperature range, max.	80 °C	Operating temperature range, min.	-5 °C
Operating temperature, max.	80 °C	Operating temperature, min.	-25 °C

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical specifications for cable

Number of poles	3	Core cross-section	0.25 mm ²
Outside diameter	4.5 mm ± 0.2 mm	Cable length	10 m
Shielded	No	Insulation	PVC
Colour coding	brown, blue, black	Sheath material	PVC
Sheathing colour	black	Halogen	Yes
Temperature range, moving	-580 °C	Temperature range, stationary	-3080 °C
Outer cladding in accordance with UL		Suitable for cable carriers	
AWM style	2464 (80 °C / 300 V)		No
Torsion resistance	0 °/m	Resistant to welding beads	No
Configurable cable length	No		

General technical data

Version	Female socket, straight	Connection thread	M12 / M8
Housing main material	PUR	Threaded ring material	Brass, nickel-plated
Coding	none	Protection degree	IP65, when screwed in
Contact surface	Gold-plated	LED	No
Rated voltage	60 V	Rated current	4 A
Insulation strength	10 ⁸ Ω	Temperature range of housing	-25+80 °C
Plugging cycles	≥ 100	Pollution severity	3
jumpered	No	-	

Standards

Connector standard	IEC 61076-2-101, IEC	Certificate no. (cULus)	
	61076-2-104		E307231

Classifications

ETIM 6.0	EC001855	ETIM 7.0	EC001855
eClass 9.0	27-06-03-11	eClass 9.1	27-06-03-11
eClass 10.0	27-06-03-11	UNSPSC	26-12-16-13

Approvals

Approvals



ROHS	Conform



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Downloads

Brochure/Catalogue	FL FIELDWIRING EN	
Engineering Data	EPLAN, WSCAD	



Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com


Drawings

Dimensioned drawing



Straight socket


Wiring diagram



Socket

Pole scheme

The ideal tool: Screwty ® with torque function





Light, securely screwed-in round plug-in connectors. Screwty set DM / VPE: 1 / Order No.: 192000000 Adapters: M12, M12 F, M8, M8 F



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Tool



Tools for stripping the sheathing from uncut power lines and outlet lines, plus screwdrivers for installing Pick-to-Light components.

General ordering data

Type SCREWTY-M12-DM
Order No. 1900001000
GTIN (EAN) 4032248436408

AN) 403224643640

Qty. 1 pc(s).

Version

Tools, Cable gland tool for moulded M12 lines

Tools



- Stripping tools with automatic self-adjustment
- For flexible and solid conductors
- Ideally suitable for mechanical and plant engineering, railway and rail traffic, wind energy, robot technology, explosion protection as well as marine, offshore and ship building sectors
- Stripping length adjustable via end stop
- Automatic opening of clamping jaws after stripping
- No fanning-out of individual conductors
- · Adjustable to diverse insulation thicknesses
- Double-insulated cables in two process steps without special adjustment
- · No play in self-adjusting cutting unit
- Long service life
- · Optimised ergonomic design

General ordering data

Type STRIPPER 6-16 RED-LINE

9203110000 St

GTIN (EAN) 4032248541423

Qty. 1 pc(s).

Order No.

Version

Stripping and cutting tool, 16mm²



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Cutting tools for outside diameters up to 22 mm



Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/IEC 60900.

General ordering data

Type KT 8
Order No. 9002650000
GTIN (EAN) 4008190020163
Oty. 1 pc(s).

Version

Cutting tools ,Cutting tool for one-hand operation

Blank



TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are five different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Preattachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the SMark laser printer, PrintJet ADVANCED, plotter, MC-Mobilo or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-lnk or STI pen in connection with CLI T sleeves

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type TM-I 18 MC NE GE
Order No. 1718431687
GTIN (EAN) 4008190349028
Qty. 320 pc(s).

Version

TM-I, Insert markers, 18 x 4 mm, yellow



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Type TM-I 18 MC NE WS
Order No. 1718431044
GTIN (EAN) 4008190349011

320 pc(s).

Version

TM-I, Insert markers, 18 x 4 mm, white

Tools

Qty.

Sheathing stripper for PVC cables



General ordering data

1 pc(s).

Type AM 12
Order No. 9030060000
GTIN (EAN) 4008190337827

Version

Tools, Sheathing strippers, UTP and STP data cables

Screwty® cable gland tool with torque function



The ideal tool for any application

Screwty® is the ideal, all-purpose tool for tightening all common sensor and actuator cables. Even difficult-to-reach round plugs are accessible using the Screwty®. A simple turning movement tightens and loosens the connectors without the need for excessive force. The Screwty® is a unique and global solution since it fits with most cables and plugs from other vendors (over 90 %). The Screwty® consists of a handle with a conventional 1/4" adapter. Thus it can be used for all sizes: for M12 and M8 round plug-in connectors, and for M12F and M8F customisable plugs and sockets, as well as for all M23 plugs and sockets.

General ordering data

Type SAI-SCREWTY BOX
Order No. 1939180000
GTIN (EAN) 4032248615506

Version

Tools, Bolting tool

Qty. 1 pc(s).