

FAD
FAD BLK1 HE20 160 M

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The front adapters for migration are connected to the old PLC and, by means of a new pre-assembled cable, to the new one. Some adapters have 2 connectors for redundancy.

General ordering data

Type	FAD BLK1 HE20 160 M
Order No.	1985950000
GTIN (EAN)	4050118370904
Qty.	1 pc(s).

**FAD
FAD BLK1 HE20 160 M**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Length	218 mm	Length (inches)	8.583 inch
Width	53.6 mm	Width (inches)	2.11 inch
Height	36.4 mm	Height (inches)	1.433 inch
Net weight	538.034 g		

Temperatures

Operating temperature, max.	50 °C	Operating temperature, min.	-25 °C
Storage temperature, max.	60 °C	Storage temperature, min.	-40 °C
Operating temperature	-25...50 °C	Storage temperature	-40...60 °C

Connection data

Connection (field side)	Plug-in connectors according to IEC 60603-13 / DIN 41651 20p
-------------------------	--

Ratings data

Operating voltage	30 V AC / 60 V DC	Max. current per channel	1 A
Max. current per byte	2 A	Total operating current	3 A

Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	< 50 V AC
Surge voltage category	III	Pollution severity level	2
Insulation test voltage	0.35 kVAC	Storage temperature, min.	-40 °C
Storage temperature, max.	60 °C		

Classifications

ETIM 6.0	EC002584	ETIM 7.0	EC002584
eClass 9.0	27-33-02-92	eClass 9.1	27-24-22-92
eClass 10.0	27-33-02-92		

Approvals

Approvals



ROHS Conform

Downloads

 Engineering Data [EPLAN](#)

Data sheet

**FAD
FAD BLK1 HE20 160 M**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

