

**FAD**  
**FAD S5115 HE20 16IO M****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

The front adapters for migration are connected to the old PLC and, by means of a new pre-assembled cable, to the new one. Some adapters have 2 connectors for redundancy.

**General ordering data**

Type	FAD S5115 HE20 16IO M
Order No.	<a href="#">1986010000</a>
GTIN (EAN)	4050118371031
Qty.	1 pc(s).

**FAD**  
**FAD S5115 HE20 16IO M**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data****Dimensions and weights**

Length	280.45 mm	Length (inches)	11.041 inch
Width	46 mm	Width (inches)	1.811 inch
Height	36.4 mm	Height (inches)	1.433 inch
Net weight	530.434 g		

**Temperatures**

Operating temperature, max.	50 °C	Operating temperature, min.	-25 °C
Storage temperature, max.	60 °C	Storage temperature, min.	-40 °C
Operating temperature	-25...50 °C	Storage temperature	-40...60 °C

**Connection data**

Connection (field side)	Plug-in connectors according to IEC 60603-13 / DIN 41651 20p
-------------------------	---

**Ratings data**

Operating voltage	30 V AC / 60 V DC	Max. current per channel	1 A
Max. current per byte	2 A	Total operating current	3 A

**Insulation coordination (EN50178)**

According to	DIN EN 50178	Rated insulation voltage	< 50 V AC
Surge voltage category	III	Pollution severity level	2
Insulation test voltage	0.35 kVAC		

**Classifications**

ETIM 6.0	EC002584	ETIM 7.0	EC002584
eClass 9.0	27-33-02-92	eClass 9.1	27-24-22-92
eClass 10.0	27-33-02-92		

**Approvals**

Approvals



ROHS Conform

**Downloads**Engineering Data [EPLAN](#)

**Data sheet**

**FAD**  
**FAD S5115 HE20 16IO M**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

