

**FAD
FAD S5135 2XHE20 32IO R**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The front adapters for migration are connected to the old PLC and, by means of a new pre-assembled cable, to the new one. Some adapters have 2 connectors for redundancy.

General ordering data

Type	FAD S5135 2XHE20 32IO R
Order No.	1986050000
GTIN (EAN)	4050118370959
Qty.	1 pc(s).

FAD
FAD S5135 2XHE20 32IO R

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Length	283 mm	Length (inches)	11.142 inch
Width	20 mm	Width (inches)	0.787 inch
Height	36.4 mm	Height (inches)	1.433 inch
Net weight	590.332 g		

Temperatures

Operating temperature, max.	50 °C	Operating temperature, min.	-25 °C
Storage temperature, max.	60 °C	Storage temperature, min.	-40 °C
Operating temperature	-25...50 °C	Storage temperature	-40...60 °C

Connection data

Connection (field side)	2 x Connector according IEC60603-13/DIN4165 1 20 p
-------------------------	--

Ratings data

Operating voltage	30 V AC / 60 V DC	Max. current per channel	1 A
Max. current per byte	2 A	Total operating current	6 A

Insulation coordination (EN50178)

According to	DIN EN 50178	Rated insulation voltage	< 50 V AC
Surge voltage category	III	Pollution severity level	2
Insulation test voltage	0.35 kVAC		

Classifications

ETIM 6.0	EC002584	ETIM 7.0	EC002584
eClass 9.0	27-33-02-92	eClass 9.1	27-24-22-92
eClass 10.0	27-33-02-92		

Approvals

Approvals



ROHS

Conform

Downloads

Engineering Data

[EPLAN](#)

Data sheet

FAD
FAD S5135 2XHE20 32IO R

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

