

SAIE-M12B-4-S-0.3U-M16**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Your peripheral devices should be supplied with greater power. With our new M12 plug-in connector, more than 250 V and 2 A is possible without problems. The compact S- and T-coded M12 plug-in connectors are designed for the transmission of up to 630 V AC or 60 V DC and 12 A.

General ordering data

Type	SAIE-M12B-4-S-0.3U-M16
Order No.	1993620000
Version	Built-in plugs, M12, Female socket, straight, M 16, Number of poles: 4, 0.3 m, Front mounting
GTIN (EAN)	4050118378634
Qty.	1 pc(s).

Creation date May 3, 2020 1:23:03 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

SAIE-M12B-4-S-0.3U-M16

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

Technical data

Dimensions and weights

Net weight	25 g
------------	------

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Standards

Connector standard	IEC 61076-2-111
--------------------	-----------------

General data

Cable glands	M 16	Cable length	0.3 m
Coding	S	Conductor O.D.	-
Connection thread	M12	Contact surface	Gold-plated
Housing main material	Zinc diecast	Number of poles	4
Plugging cycles	≥ 100	Protection degree	IP67, when screwed in
Rated current	12 A	Strand / cable length	0.3 m

Classifications

ETIM 6.0	EC002635	ETIM 7.0	EC003570
eClass 9.0	27-44-01-03	eClass 9.1	27-44-01-03
eClass 10.0	27-44-01-03		

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	FL FIELDWIRING EN
Engineering Data	STEP

Data sheet

SAIE-M12B-4-S-0.3U-M16

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

Pole scheme

