

**VPK EX 7J (Ex blanking plug, plastic, 7J)
VP M25 EX SI 7J**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Similar to illustration

For sealing surplus threaded holes to maintain the IP class of protection

General ordering data

Type	VP M25 EX SI 7J
Order No.	2066740000
Version	VPK EX 7J (Ex blanking plug, plastic, 7J), Blanking plug, M 25, 10 mm, IP54, IP66, IP67, IP68 - 5 bar (30 min.), Polyamide 6
GTIN (EAN)	4050118415360
Qty.	100 pc(s).

Creation date May 2, 2020 10:19:15 PM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**VPK EX 7J (Ex blanking plug, plastic, 7J)
VP M25 EX SI 7J**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Length	15.8 mm	Length (inches)	0.622 inch
Height	15.8 mm	Height (inches)	0.622 inch
Net weight	5 g		

General information

Material	Polyamide 6	External thread	M 25
Pitch of thread	1.5 mm	Length of thread	10 mm
AF size 1	28 mm	AF size 2	28 mm
Impact resistance	7 joules in acc. with IEC 60079-0	Protection degree	IP54, IP66, IP67, IP68 - 5 bar (30 min.)
Protection degree with GWDR	IP54, IP66, IP67, IP68 - 5 bar (30 min.)	Operating temperature range, min.	-60 °C
Operating temperature range, max.	70 °C	O-Ring	Silicone
Sealing	Silicone	Torque for connecting adapter, min.	2.5 Nm
Torque for connecting adapter, max.	2.5 Nm	Torque for lock nut, min.	2.3 Nm
Torque for lock nut, max.	2.5 Nm	Explosion protection type	Improved safety Ex e
Standards	IEC 60079-0, EN 60079-0, IEC 60079-7, EN 60079-7, EN 60079-31, IEC 60079-31	Installation guidelines	See assembly instructions

Classifications

ETIM 6.0	EC000451	ETIM 7.0	EC000451
eClass 9.0	27-14-44-25	eClass 9.1	27-14-44-35
eClass 10.0	27-14-44-25		

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN
Engineering Data	STEP

**VPK EX 7J (Ex blanking plug, plastic, 7J)
VP M25 EX SI 7J**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories

Brass nuts, standard, nickel-plated



Weidmüller has a variety of different cable and wire entry systems in the Portfolio: with different designs of plastic, brass and stainless steel cable glands in the IP66, 67, 68 or IP69k protection classes. As a complete alternative to cable glands, pre-assembled cables with modular multi-wire or multi-cable entry systems can be simply and quickly inserted into electrical equipment. Last but not least, Weidmüller offers EX-certified cable glands and cable/wire entry systems.

- Cable glands made from plastic and brass
- EMC screwed joints
- for areas at risk of explosion
- VDE, CSA and UL approvals

General ordering data

Type	SKMU M25 MS	Version	
Order No.	1737010000		SKMU MS (brass locknut), Locknut, M 25, 3 mm, Brass, nickel-plated
GTIN (EAN)	4008190956486		
Qty.	100 pc(s).		