

**ClipCard  
CC 85/27 K MC NE SI**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com



ClipCard device markers in MultiCard format are used for labelling electrical installations and switchgear systems, and offer an interesting alternative to engraving. Thanks to the proven MultiCard format, labelling is possible with PrintJet PRO, the MCP Plus plotter, MCP Basis and MC-Mobilo.

- Highly resistant printing quality when using the PrintJet as a substitute for engraving
- Universal fixing
- Carrier (screwable or with cable ties)
- Tag rail (self-adhesive or screw fixing)
- Or self-adhesive tags

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Please note that these markers are not intended for printing with the SpeedMarking laser.

**General ordering data**

|                    |  |
|--------------------|--|
| Type               | CC 85/27 K MC NE SI  |
| Order No.          | <a href="#">2123070000</a>   |
| Version            | ClipCard, Device markers, 27 x 85 mm, silver                                     |
| GTIN (EAN)         | 4050118425505  |
| Qty.               | 20 pc(s).  |
| compatible printer | <a href="#">1324380000</a> <a href="#">2438520000</a> <a href="#">2438510000</a> |

## Data sheet

### ClipCard CC 85/27 K MC NE SI

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

## Technical data

### Dimensions and weights

|            |        |                 |            |
|------------|--------|-----------------|------------|
| Width      | 85 mm  | Width (inches)  | 3.346 inch |
| Height     | 27 mm  | Height (inches) | 1.063 inch |
| Depth      | 0.8 mm | Depth (inches)  | 0.031 inch |
| Net weight | 7.37 g |                 |            |

### General data

|                             |                            |                        |               |
|-----------------------------|----------------------------|------------------------|---------------|
| Adhesive                    | Double-sided adhesive tape | Colour                 | silver        |
| Halogen                     | No                         | Material               | Polyamide 66  |
| Operating temperature range | -40...60 °C                | Recommended industries | Machinery     |
| UL 94 flammability rating   | V-2                        | Version                | Self-adhesive |
| Width                       | 85 mm                      |                        |               |

### Classifications

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC001288    | ETIM 7.0   | EC001288    |
| eClass 9.0  | 27-40-06-29 | eClass 9.1 | 27-40-06-29 |
| eClass 10.0 | 27-40-06-29 |            |             |

### Approvals

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

### Downloads

|                  |                       |
|------------------|-----------------------|
| Engineering Data | <a href="#">EPLAN</a> |
|------------------|-----------------------|

**Data sheet**

**ClipCard  
CC 85/27 K MC NE SI**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

