

**CMA-1056-1500-5A-10VA-1****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



The pluggable current transformers are particularly suitable for installation on the busbar.

Advantages:

- Screwless connection system with tension-clamp terminal.
- Time-saving connection option for solid and flexible conductors.
- Shock-proof and resistant to vibration, high mechanical retention forces.
- High current resistance

**General ordering data**

Delivery status	<b>This article will no longer be available in the future.</b>
Available until	2020-01-31
Type	CMA-1056-1500-5A-10VA-1
Order No.	<a href="#">2420810000</a>
GTIN (EAN)	4050118429053
Qty.	1 pc(s).

Creation date May 2, 2020 7:09:01 PM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

## CMA-1056-1500-5A-10VA-1

Weidmüller Interface GmbH &amp; Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

## Technical data

## Dimensions and weights

Width	129 mm	Width (inches)	5.079 inch
Height	167 mm	Height (inches)	6.575 inch
Depth	78 mm	Depth (inches)	3.071 inch
Net weight	1 g		

## Temperatures

Operating temperature, max.	40 °C	Operating temperature, min.	-5 °C
Storage temperature, max.	40 °C	Storage temperature, min.	-25 °C
Operating temperature	-5 °C...40 °C	Storage temperature	-25 °C...40 °C

## Dimensions of live conductors

Installation location	Indoor use	Rail	100 x 55 mm
Round conductor	55 mm	Type of conductor	Insulated conductor only

## Technical data

Insulation class	E	Nominal frequency	50 Hz
Operating voltage $U_{\max}$ , max.	0.72 kV	Thermal rated continuous current $I_{\text{thermal}}$	$1.0 \times I_{\text{rated}}$

## Technical properties

Insulation class	E	Nominal frequency	50 Hz
Operating voltage $U_{\max}$ , max.	0.72 kV	Thermal rated continuous current $I_{\text{thermal}}$	$1.0 \times I_{\text{rated}}$

## Electrical attributes

Load	10 VA	Primary current	1,500 A
Secondary current max.	5 A	Tolerance class	1

## Classifications

ETIM 6.0	EC002048	ETIM 7.0	EC002048
eClass 9.0	27-21-09-02	eClass 9.1	27-21-09-02
eClass 10.0	27-21-09-02		

## Approvals

ROHS	Conform
------	---------

## Downloads

User Documentation	<a href="#">Instruction sheet</a>
--------------------	-----------------------------------

**CMA-1056-1500-5A-10VA-1**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Drawings**

