

## Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Similar to illustration**





Weidmüller is one of the industry's leading international providers of connectors. An important mainstay in this product family are the circular connectors, which Weidmüller groups under the product name SAI. In the development of SAI products, Weidmüller engineers have always concentrated on achieving rational, cost-effective installation concepts, and – in cooperation with major users – have supplied the markets with well-conceived products which set standards in terms of functionality and quality across the globe. The best examples are the new power distributors with S and T coded M12. These modules are characterised by particularly high currents and voltages. This enables them to also be used, for example, with three-phase motors.

#### **General ordering data**

Туре	SAID-M12S-8-9SMT
Order No.	<u>2422420000</u>
Version	Built-in plugs, M12, Pin, Number of poles: 8
GTIN (EAN)	4050118430738
Qty.	25 pc(s).

## Creation date May 2, 2020 6:43:10 PM CEST

# **Technical data**



## Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Dimensions and weigh	ts		
Net weight	3.76 g		
Environmental Product	t Compliance		
REACH SVHC	Lead 7439-92-1		
Technical data of PCB	plug-in connector		
Coding	A	Housings	M12 pin
Number of poles	8	Shield connection	No
Rated voltage	30 V	Rated voltage (text)	250 V (4-pole) / 60 V (5 pole) / 30 V (8-pole)
Rated current	2 A	Rated current	4 A (4- and 5-pole) / 2 A (8-pole)
Temperature range	-2595 °C	Protection degree	IP67
Contact surface	Au (Gold)	Housing main material	LCP
Connection thread	M12	Tightening torque	M12: 0.8 Nm
Insulation strength	100 MΩ	Pollution severity	3 (2 within the sealed area)
Plugging cycles	≥ 100	Contact material	CuZn
Lock nut material	Nickel-plated CuZn	Material of the flange-mounted housing	Nickel-plated CuZn
Material data			
Contact material	CuZn	Contact surface	Au (Gold)
System parameters			
Insulation strength	100 MΩ	Number of poles	8
Pin series quantity	1	Plugging cycles	≥ 100
Protection degree	IP67		
Classifications			
ETIM 6.0	EC000438	ETIM 7.0	EC000438
eClass 9.1	27-44-02-05	eClass 10.0	27-44-02-23
Approvals			
ROHS	Conform		
Downloads	Contoint		
Brochure/Catalogue	<u>FL FIELDWIRING EN</u>		


Creation date May 2, 2020 6:43:10 PM CEST

# Drawings




## Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com



PCB design



## Pole scheme



# Accessories

### Accessories



## Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Weidmüller is one of the industry's leading international providers of connectors. An important mainstay in this product family are the circular connectors, which Weidmüller groups under the product name SAI. In the development of SAI products, Weidmüller engineers have always concentrated on achieving rational, cost-effective installation concepts, and – in cooperation with major users – have supplied the markets with well-conceived products which set standards in terms of functionality and quality across the globe. The best examples are the new power distributors with S and T coded M12. These modules are characterised by particularly high currents and voltages. This enables them to also be used, for example, with three-phase motors.

## **General ordering data**

Туре	SAIE-KMM14X1-SW15	Version
Order No.	<u>2424010000</u>	Locknut
GTIN (EAN)	4050118431230	
Qty.	25 pc(s).	
Туре	SAIFG-M14X1-S-1	Version
Type Order No.	SAIFG-M14X1-S-1 2423980000	Version Built-in plug housing, M12 pin, Mounting height: 9 mm