

**PAC-D37F-F-HF-9M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com



Similar to illustration

Cable pre-confeccionado sub-d según IEC-807/  
DIN41652

- Sub-d a Sub-d
- Sub-d a punteras
- Cable apantallado

**General ordering data**

Type	PAC-D37F-F-HF-9M
Order No.	<a href="#">2426050090</a>
Version	
GTIN (EAN)	4032248330867
Qty.	1 pc(s).

Creation date May 2, 2020 5:26:00 PM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**PAC-D37F-F-HF-9M****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0

Fax: +49 5231 14-292083

www.weidmueller.com

**Technical data****Dimensions and weights**

Net weight	2,671 g
------------	---------

**Temperatures**

Operating temperature, max.	50 °C	Operating temperature, min.	-10 °C
Storage temperature, max.	60 °C	Storage temperature, min.	-10 °C
Operating temperature	-10...50 °C	Storage temperature	-10...60 °C

**General Data**

Connector PLC side	H0.25/10 (FERRULES 0.25mm <sup>2</sup> )	Interface connector	SUB-D FEMALE 37P
Number of poles, min.	37-pole	Cable length	9 m
Wire cross-section	0.25 mm <sup>2</sup>		

**Electrical Data**

Rated voltage (text)	≤ 60 Vdc ≤ 25 Vac	Permissible current strength per path, max.	1 A
Total current, max.	3 A	Resistance	≤ 80 mΩ/m

**Classifications**

ETIM 6.0	EC000237	ETIM 7.0	EC000237
eClass 9.0	27-24-22-20	eClass 9.1	27-24-22-20
eClass 10.0	27-24-22-20		

**Approvals**

ROHS	Conform
------	---------